

BELVEDERE CLOVE I

100° Beam angle **Mounting** Ground

Power LED: 8,4W - 873 lm ≠ FIXT 703 lm - 4000K/CRI 80 - 100-240V Lamps description

Environment Outdoor

Notes We recommend using a connection system with a degree of

protection greater than or equal to the degree of protection

of the luminaire.

Technical description

Family of outdoor products consisting of luminaires with a pole of two different heights and suitable for floor installations (ground or buried) and with integrated power supply box.

ELECTRICAL

Transformer type Electronic Transformer availability Included **Transformer mounting** Integral **Emergency** Without 110/240 Voltage (V)

PHYSICAL

Aiming Fixed 1.70 Weight (kg) **Number of heads** ı





Belvedere Clove I

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).

F001A41A001 White F001A41A006 Grey F001A41A033 Anthracite F001A41A030 Black F001A41A018 Deep brown

DIMENSIONS




CERTIFICATIONS













Belvedere Clove I . Accessories


Mounting



F001Z020000

Box for ground installation

Electrical



F990E00A000

Surge protection device

Surge protection device. 275Vac. Maximum discharge current 10KA (8/20us). Maximum operating current 5A. Suitable for series connection. IP66.




Belvedere Clove I

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).

F001A41A001 White
F001A41A006 Grey
F001A41A033 Anthracite
F001A41A030 Black
F001A41A018 Deep brown

DIMENSIONS




CERTIFICATIONS













Belvedere Clove I . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED



Belvedere Clove I

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).

F001A41A001 White

F001A41A006 Grey

F001A41A033 Anthracite

F001A41A030 Black

F001A41A018 Deep brown

DIMENSIONS



CERTIFICATIONS









