

BELVEDERE SPOT F2 DIMMABLE I-10V

Beam angle	28° Flood
Mounting	Ground
Lamps description	Power LED: 6W - 513 lm ≠ FIXT 351 lm - 2700K/CRI 80 - 100-240V
Environment	Outdoor
Notes	We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.
Technical description	Family of adjustable outdoor LED lighting luminaires (double rotation, vertical and horizontal axle) suitable for floor installations (ground or buried) and with integrated power supply box.



Belvedere Spot F2 Dimmable I-10V

designed by Antonio Citterio with Toan Nguyen

ELECTRICAL

Transformer type	Electronic dimmable I-10V
Transformer availability	Included
Transformer mounting	Integral
Emergency	Without
Voltage (V)	100/240

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).


PHYSICAL

Aiming	Adjustable
Weight (kg)	1,70
Number of heads	1


- F001D23B001 White
- F001D23B006 Grey
- F001D23B033 Anthracite
- F001D23B030 Black
- F001D23B018 Deep brown



DIMENSIONS



CERTIFICATIONS



Belvedere Spot F2 Dimmable I-10V .Accessories

Optical



F001Z010000

Spot visor



F001Z030000

Spot visor with honeycomb



F001Z040000

Spot visor with flood lens




Belvedere Spot F2 Dimmable I-10V

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).

- F001D23B001 White
- F001D23B006 Grey
- F001D23B033 Anthracite
- F001D23B030 Black
- F001D23B018 Deep brown

DIMENSIONS




Mounting



F001Z020000


Box for ground installation

CERTIFICATIONS



Belvedere Spot F2 Dimmable I-10V .Accessories

Electrical



○ F990E00A000

Surge protection device

Surge protection device.
275Vac. Maximum discharge current 10KA (8/20us).
Maximum operating current 5A. Suitable for series connection. IP66.



Belvedere Spot F2 Dimmable I-10V

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included.
Ready for installation on rigid base.
Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).

- F001D23B001 White
- F001D23B006 Grey
- F001D23B033 Anthracite
- F001D23B030 Black
- F001D23B018 Deep brown

Belvedere Spot F2 Dimmable I-10V .Lamps



Power LED

Lamp category:

LED


Socket:

Special base

Lamp type:

Power LED

DIMENSIONS



CERTIFICATIONS

