

BELVEDERE SPOT F3 DIMMABLE 1-10V

Beam angle 10° Spot **Mounting** Ground

Power LED: 6W - 513 lm ≠ FIXT 425 lm - 2700K/CRI 80 - 100-240V Lamps description

Environment Outdoor

Notes We recommend using a connection system with a degree of

protection greater than or equal to the degree of protection

of the luminaire.

Technical description Family of adjustable outdoor LED lighting luminaires (double

rotation, vertical and horizontal axle) suitable for floor installations

(ground or buried) and with integrated power supply box.

ELECTRICAL

Transformer type Electronic dimmable I-10V

Transformer availability Included **Transformer mounting** Integral **Emergency** Without 100/240 Voltage (V)

PHYSICAL

Aiming Adjustable Weight (kg) 2,10 **Number of heads**




Belvedere Spot F3 Dimmable I-I0V

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).

F001E21B001 White F001E21B006 Grey F001E21B033 Anthracite F001E21B030 Black F001E21B018 Deep brown

DIMENSIONS




CERTIFICATIONS











Belvedere Spot F3 Dimmable I-10V . Accessories

Optical





F001Z030000



F001Z010000

Spot visor Spot visor with honeycomb

F001Z040000

Spot visor with flood lens

Mounting



F001Z020000

Box for ground installation




Belvedere Spot F3 Dimmable I-I0V

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).

F001E21B001 White
F001E21B006 Grey
F001E21B033 Anthracite
F001E21B030 Black
F001E21B018 Deep brown

DIMENSIONS




CERTIFICATIONS














Belvedere Spot F3 Dimmable I-10V . Accessories

Electrical



F990E00A000

Surge protection device

Surge protection device. 275Vac. Maximum discharge current 10KA (8/20us). Maximum operating current 5A. Suitable for series connection. IP66.

Belvedere Spot F3 Dimmable I-10V . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




Belvedere Spot F3 Dimmable I-I0V

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).

F001E21B001 White
F001E21B006 Grey
F001E21B033 Anthracite
F001E21B030 Black
F001E21B018 Deep brown

DIMENSIONS



CERTIFICATIONS









