FLOS

BELVEDERE SPOT F3

Beam angle	10° Spot
Mounting	Ground
Lamps description	Power LED: 6W - 530 lm ≠ FIXT 440 lm - 3000K/CRI 80 - 100-240V
Environment	Outdoor
Notes	We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.
Technical description	Family of adjustable outdoor LED lighting luminaires (double rotation, vertical and horizontal axle) suitable for floor installations

(ground or buried) and with integrated power supply box.

ELECTRICAL

Transformer type
Transformer availability
Transformer mounting
Emergency
Voltage (V)

Electronic Included Integral Without 100/240

PHYSICAL

Aiming	
Weight (kg)	
Number of heads	

Adjustable 2,10 1







Belvedere Spot F3

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).







FLOS

Belvedere Spot F3 . Accessories

Optical



F001Z010000

Spot visor

F001Z030000

Spot visor with honeycomb



F001Z040000


Spot visor with flood lens




Belvedere Spot F3

designed by Antonio Citterio with Toan Nguyen


100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).





CERTIFICATIONS





Mounting




F001Z020000

Box for ground installation

FLOS

Belvedere Spot F3 . Accessories

Electrical



F990E00A000

Surge protection device

Surge protection device. 275Vac. Maximum discharge current 10KA (8/20us). Maximum operating current 5A. Suitable for series connection. IP66.

Belvedere Spot F3 . Lamps



Power LED

Lamp category: LED Socket: Special base


Lamp type: Power LED



Belvedere Spot F3

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).



CERTIFICATIONS



