

BELVEDERE SPOT F3 DALI

Beam angle 10° Spot **Mounting** Ground

Lamps description Power LED: 6W - 530 lm ≠ FIXT 440 lm - 3000K/CRI 80 - 100-240V

Environment Outdoor

Notes We recommend using a connection system with a degree of

protection greater than or equal to the degree of protection

of the luminaire.

Technical description

Family of adjustable outdoor LED lighting luminaires (double

rotation, vertical and horizontal axle) suitable for floor installations

(ground or buried) and with integrated power supply box.

ELECTRICAL

Transformer type Electronic dimmable dali

Transformer availability Included
Transformer mounting Integral
Emergency Without
Voltage (V) 100/240

PHYSICAL

Aiming Adjustable
Weight (kg) 2,10
Number of heads I




Belvedere Spot F3 Dali

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).

F001E31D001 White
F001E31D006 Grey
F001E31D033 Anthracite
F001E31D030 Black
F001E31D018 Deep brown

DIMENSIONS




CERTIFICATIONS











Belvedere Spot F3 Dali . Accessories

Optical







F001Z010000

Spot visor

F001Z030000

Spot visor with

honeycomb

F001Z040000

Spot visor with flood lens

Mounting



F001Z020000

Box for ground installation




Belvedere Spot F3 Dali

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).

F001E31D001 White
F001E31D006 Grey
F001E31D033 Anthracite
F001E31D030 Black
F001E31D018 Deep brown

DIMENSIONS




CERTIFICATIONS














Belvedere Spot F3 Dali . Accessories

Electrical



F990E00A000

Surge protection device

Surge protection device. 275Vac. Maximum discharge current 10KA (8/20us). Maximum operating current 5A. Suitable for series connection. IP66.

Belvedere Spot F3 Dali . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




Belvedere Spot F3 Dali

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).

F001E31D001 White
F001E31D006 Grey
F001E31D033 Anthracite
F001E31D030 Black
F001E31D018 Deep brown

DIMENSIONS



CERTIFICATIONS









