

BELVEDERE SPOT F3

Beam angle 16° Medium **Mounting** Ground

Lamps description Power LED: 6W - 530 lm ≠ FIXT 393 lm - 3000K/CRI 80 - 100-240V

Environment Outdoor

Notes We recommend using a connection system with a degree of

protection greater than or equal to the degree of protection

of the luminaire.

Technical descriptionFamily of adjustable outdoor LED lighting luminaires (double rotation, vertical and horizontal axle) suitable for floor installations

(ground or buried) and with integrated power supply box.

ELECTRICAL

Transformer type Electronic
Transformer availability Included
Transformer mounting Integral
Emergency Without
Voltage (V) 100/240

PHYSICAL

Aiming Adjustable
Weight (kg) 2,10
Number of heads I




Belvedere Spot F3

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).

F001E32A001 White
F001E32A006 Grey
F001E32A033 Anthracite
F001E32A030 Black
F001E32A018 Deep brown

DIMENSIONS




CERTIFICATIONS









FLOS

Belvedere Spot F3. Accessories

Optical





F001Z030000



F001Z010000

Spot visor

Spot visor with honeycomb

F001Z040000

Spot visor with flood lens

Mounting



F001Z020000

Box for ground installation


Belvedere Spot F3

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).

F001E32A001 White
F001E32A006 Grey
F001E32A033 Anthracite
F001E32A030 Black
F001E32A018 Deep brown

DIMENSIONS




CERTIFICATIONS














Belvedere Spot F3. Accessories

Electrical



F990E00A000

Surge protection device

Surge protection device. 275Vac. Maximum discharge current 10KA (8/20us). Maximum operating current 5A. Suitable for series connection. IP66.

Belvedere Spot F3 . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




Belvedere Spot F3

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).

F001E32A001 White
F001E32A006 Grey
F001E32A033 Anthracite
F001E32A030 Black
F001E32A018 Deep brown

DIMENSIONS



CERTIFICATIONS









