

#### **BELVEDERE SPOT F3 DIMMABLE 1-10V**

Beam angle16° MediumMountingGround

**Lamps description** Power LED: 6W - 530 lm ≠ FIXT 393 lm - 3000K/CRI 80 - 100-240V

**Environment** Outdoor

**Notes** We recommend using a connection system with a degree of

protection greater than or equal to the degree of protection

of the luminaire.

**Technical description** Family of adjustable outdoor LED lighting luminaires (double

rotation, vertical and horizontal axle) suitable for floor installations

(ground or buried) and with integrated power supply box.

#### **ELECTRICAL**

Transformer type Electronic dimmable 1-10V

Transformer availability Included
Transformer mounting Integral
Emergency Without
Voltage (V) 100/240

#### **PHYSICAL**

Aiming Adjustable
Weight (kg) 2,10
Number of heads I




#### Belvedere Spot F3 Dimmable I-I0V

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).

F001E32B001 White
F001E32B006 Grey
F001E32B033 Anthracite
F001E32B030 Black
F001E32B018 Deep brown

### **DIMENSIONS**




#### **CERTIFICATIONS**











## Belvedere Spot F3 Dimmable I-10V . Accessories

## **Optical**





F001Z030000



F001Z010000

Spot visor Spot visor with honeycomb

F001Z040000

Spot visor with flood lens

## Mounting



F001Z020000

Box for ground installation




## Belvedere Spot F3 Dimmable I-I0V

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).

F001E32B001 White
F001E32B006 Grey
F001E32B033 Anthracite
F001E32B030 Black
F001E32B018 Deep brown

## **DIMENSIONS**




#### **CERTIFICATIONS**














## Belvedere Spot F3 Dimmable I-10V . Accessories

#### **Electrical**



# F990E00A000

#### Surge protection device

Surge protection device. 275Vac. Maximum discharge current 10KA (8/20us). Maximum operating current 5A. Suitable for series connection. IP66.

## Belvedere Spot F3 Dimmable I-10V . Lamps



## **Power LED**

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




## Belvedere Spot F3 Dimmable I-I0V

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).

F001E32B001 White
F001E32B006 Grey
F001E32B033 Anthracite
F001E32B030 Black
F001E32B018 Deep brown

## **DIMENSIONS**



#### **CERTIFICATIONS**









