FLOS

BELVEDERE SPOT F3 DIMMABLE 1-10V

Beam angle Mounting	28° Flood Ground
Lamps description	Power LED: 6W - 570 lm ≠ FIXT 390 lm - 4000K/CRI 80 - 100-240V
Environment	Outdoor
Notes	We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.
Technical description	Family of adjustable outdoor LED lighting luminaires (double rotation, vertical and horizontal axle) suitable for floor installations (ground or buried) and with integrated power supply box.

Belvedere Spot F3 Dimmable I-I0V

designed by Antonio Citterio with Toan Nguyen

ELECTRICAL Transformer type


Electronic dimmable 1-10V Included Integral Without 100/240

PHYSICAL

Aiming Weight (kg) Number of heads Adjustable 2,10 1




100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).





CERTIFICATIONS





FLOS

Belvedere Spot F3 Dimmable 1-10V . Accessories

Optical



F001Z010000

Spot visor



F001Z030000

Spot visor with honeycomb



F001Z040000


Spot visor with flood lens




Belvedere Spot F3 Dimmable I-I0V

designed by Antonio Citterio with Toan Nguyen


100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).





CERTIFICATIONS





Mounting




F001Z020000

Box for ground installation

FLOS

Belvedere Spot F3 Dimmable 1-10V .Accessories

Electrical



F990E00A000

Surge protection device

Surge protection device. 275Vac. Maximum discharge current 10KA (8/20us). Maximum operating current 5A. Suitable for series connection. IP66.

Belvedere Spot F3 Dimmable 1-10V . Lamps



Power LED

Lamp category: LED Socket: Special base

Lamp type: Power LED



Belvedere Spot F3 Dimmable 1-10V

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Ready for installation on rigid base. Box for ground installation to be ordered separately. Included 2 way terminal block 3 phases IP68 (7-12 mm cable).

