

#### **BELVEDERE SPOT PICK**

**Beam angle** 16° Medium **Mounting** Ground spike

**Lamps description** Power LED: 6W - 513 lm ≠ FIXT 380 lm - 2700K/CRI 80 - 100-240V

**Environment** Outdoor

**Notes** We recommend using a connection system with a degree of

protection greater than or equal to the degree of protection

of the luminaire.

Technical description
Family of adjustable outdoor LED lighting luminaires (double

rotation, vertical and horizontal axle) suitable for floor installations

(ground or buried) and with integrated power supply box.

#### **ELECTRICAL**

Transformer type Electronic
Transformer availability Included
Transformer mounting Integral
Emergency Without
Voltage (V) 100/240

#### **PHYSICAL**

Aiming Adjustable
Weight (kg) 1,05
Number of heads I






## **Belvedere Spot Pick**

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Included 2 way terminal block 3 phases IP68 (7-12 mm cable). 24V Dimmable version available on request.

F001F22A001 White
F001F22A006 Grey
F001F22A033 Anthracite
F001F22A030 Black
F001F22A018 Deep brown

#### **DIMENSIONS**




#### **CERTIFICATIONS**











# **FLOS**

## **Belvedere Spot Pick . Accessories**

## **Optical**







F001Z010000

Spot visor

F001Z030000

Spot visor with

honeycomb

F001Z040000

Spot visor with flood lens

## Mounting



F001Z020000

Box for ground installation




#### **Belvedere Spot Pick**

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Included 2 way terminal block 3 phases IP68 (7-12 mm cable). 24V Dimmable version available on request.

F001F22A001 White
F001F22A006 Grey
F001F22A033 Anthracite
F001F22A030 Black
F001F22A018 Deep brown

#### **DIMENSIONS**




#### **CERTIFICATIONS**














## **Belvedere Spot Pick . Accessories**

#### **Electrical**



### F990E00A000

#### Surge protection device

Surge protection device. 275Vac. Maximum discharge current 10KA (8/20us). Maximum operating current 5A. Suitable for series connection. IP66.

#### **Belvedere Spot Pick. Lamps**



#### **Power LED**

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




## **Belvedere Spot Pick**

designed by Antonio Citterio with Toan Nguyen

100/240V power supply included. Included 2 way terminal block 3 phases IP68 (7-12 mm cable). 24V Dimmable version available on request.

F001F22A001 White
F001F22A006 Grey
F001F22A033 Anthracite
F001F22A030 Black
F001F22A018 Deep brown

#### **DIMENSIONS**



#### **CERTIFICATIONS**









