

## BELVEDERE SPOT WALL

<b>Beam angle</b>	10° Spot
<b>Mounting</b>	Wall surface
<b>Lamps description</b>	Power Led: 6W - 530 lm ≠ FIXT 440 lm - 3000K/CRI 80 - 100-240V
<b>Environment</b>	Outdoor
<b>Notes</b>	We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.
<b>Technical description</b>	Outdoor luminaire consisting of an adjustable projector for up to 350°±5° on the horizontal axle suitable for wall installations and with integrated power supply box.




### Belvedere Spot Wall

designed by Antonio Citterio with Toan Nguyen



Direct wall attachment. 100/240V power supply included. Included 2 way terminal block 3 phases IP68 (7-12 mm cable). 24V Dimmable version available on request.

- F001G31A001 White
- F001G31A006 Grey
- F001G31A033 Anthracite
- F001G31A030 Black
- F001G31A018 Deep brown

### DIMENSIONS



### CERTIFICATIONS



## Belvedere Spot Wall .Accessories

### Optical



○ F001Z010000

**Spot visor**



○ F001Z030000

**Spot visor with honeycomb**



○ F001Z040000

**Spot visor with flood lens**




### Belvedere Spot Wall

designed by Antonio Citterio with Toan Nguyen

Direct wall attachment. 100/240V power supply included. Included 2 way terminal block 3 phases IP68 (7-12 mm cable). 24V Dimmable version available on request.

- F001G31A001 White
- F001G31A006 Grey
- F001G31A033 Anthracite
- F001G31A030 Black
- F001G31A018 Deep brown

### DIMENSIONS




### Mounting



○ F001Z020000


**Box for ground installation**

### CERTIFICATIONS



## Belvedere Spot Wall . Accessories

### Electrical



○ F990E00A000

### Surge protection device

Surge protection device. 275Vac. Maximum discharge current 10KA (8/20us). Maximum operating current 5A. Suitable for series connection. IP66.




### Belvedere Spot Wall

designed by Antonio Citterio with Toan Nguyen

Direct wall attachment. 100/240V power supply included. Included 2 way terminal block 3 phases IP68 (7-12 mm cable). 24V Dimmable version available on request.

- F001G31A001 White
- F001G31A006 Grey
- F001G31A033 Anthracite
- F001G31A030 Black
- F001G31A018 Deep brown

### DIMENSIONS



### CERTIFICATIONS



## Belvedere Spot Wall . Lamps



### Power LED

### Lamp category:

LED

### Socket:

Special base

### Lamp type:

Power LED

