FLOS

BELLHOP H 380 MM

85° Floor

Power LED: 8W - 783 lm ≠ FIXT 551 lm - 2700K/CRI 80 - 100-240V Outdoor


Bollard version of the Bellhop Outdoor Collection for diffuse light. Made of extruded and die-cast aluminium or stainless steel, Bellhop is available in two heights for the bollard model and with different lumens and luminaire outputs as to comply with any outdoor setting and lighting scenario need.</

Bellhop H 380 mm

designed by Edward Barber and Jay Osgerby




DIMENSIONS



CERTIFICATIONS





| ELECTRICAL | |
|--------------------------|------------|
| Transformer type | Electronic |
| Transformer availability | Included |
| Transformer mounting | Integral |
| Emergency | Without |
| Voltage (V) | 100/240 |
| | |

PHYSICAL

Aiming Weight (kg) Number of heads Fixed 1,20 (2,20 Kg Stainless Steel) 1



www.flos.com info@flos.it

FLOS

Bellhop H 380 mm . Accessories

Electrical



FI205000

2 way terminal block 3 poles IP68 7-12 mm cables

Structural





Base plate with bolt




Bellhop H 380 mm

designed by Edward Barber and Jay Osgerby

100/240V power supply included. Ready for installation on rigid base. Each luminaire is equipped with a segment of 20 cm cable for connection inside the luminaire body. Suggested connection with 2 way terminal block 3 phases IP68, to be ordered separately.




DIMENSIONS



CERTIFICATIONS





www.flos.com info@flos.it

FLOS

Bellhop H 380 mm . Lamps



Power LED

Lamp category: LED Socket: Special base Lamp type: Power LED




Bellhop H 380 mm

designed by Edward Barber and Jay Osgerby

100/240V power supply included. Ready for installation on rigid base. Each luminaire is equipped with a segment of 20 cm cable for connection inside the luminaire body. Suggested connection with 2 way terminal block 3 phases IP68, to be ordered separately.




DIMENSIONS



CERTIFICATIONS





www.flos.com info@flos.it