# FLOS

#### **BELLHOP H 850 MM DALI**

85°

span>

Beam angle
Mounting
Lamps description
Environment
Technical description

Floor Power LED: 8W - 783 Im ≠ FIXT 551 Im - 2700K/CRI 80 - 100-240V Outdoor Bollard version of the Bellhop Outdoor Collection for diffuse light. Made of extruded and die-cast aluminium or stainless steel, Bellhop is available in two heights for the bollard model and with different lumens and luminaire outputs as to comply with any <span>outdoor setting and lighting scenario need.</

#### Bellhop H 850 mm Dali

designed by Edward Barber and Jay Osgerby

### ELECTRICAL

Transformer type
Transformer availability
Transformer mounting
Emergency
Voltage (V)

Electronic dimmable dali Included Integral Without 100/240

### PHYSICAL


Aiming Weight (kg) Number of heads Fixed 1,80 (3 Kg Stainless Steel)



100/240V power supply included. Ready for installation on rigid base. Each luminaire is equipped with a segment of 20 cm cable for connection inside the luminaire body. Suggested connection with 2 way terminal block 3 phases IP68, to be ordered separately.




#### DIMENSIONS



CERTIFICATIONS





www.flos.com info@flos.it

# FLOS

#### Bellhop H 850 mm Dali .Accessories

#### Electrical



FI205000

2 way terminal block 3 poles IP68 7-12 mm cables

#### Structural





Base plate with bolt




#### Bellhop H 850 mm Dali

designed by Edward Barber and Jay Osgerby

100/240V power supply included. Ready for installation on rigid base. Each luminaire is equipped with a segment of 20 cm cable for connection inside the luminaire body. Suggested connection with 2 way terminal block 3 phases IP68, to be ordered separately.




#### DIMENSIONS



#### CERTIFICATIONS





www.flos.com info@flos.it

### FLOS

Bellhop H 850 mm Dali . Lamps



Power LED

Lamp category: LED Socket: Special base Lamp type: Power LED




#### Bellhop H 850 mm Dali

designed by Edward Barber and Jay Osgerby

100/240V power supply included. Ready for installation on rigid base. Each luminaire is equipped with a segment of 20 cm cable for connection inside the luminaire body. Suggested connection with 2 way terminal block 3 phases IP68, to be ordered separately.




#### DIMENSIONS



#### CERTIFICATIONS





www.flos.com info@flos.it