

BELLHOP H 850 MM

Beam angle 85° **Mounting** Floor

Lamps description Power LED: 8W - 816 lm ≠ FIXT 580 lm - 3000K/CRI 80 - 100-240V

Environment Outdoor

Technical descriptionBollard version of the Bellhop Outdoor Collection for diffuse

light. Made of extruded and die-cast aluminium or stainless steel, Bellhop is available in two heights for the bollard model and with different lumens and luminaire outputs as to comply with any outdoor setting and lighting scenario need.</

span>

ELECTRICAL


Transformer type Electronic
Transformer availability Included
Transformer mounting Integral
Emergency Without
Voltage (V) 100/240

PHYSICAL

Aiming Fixed

Weight (kg) 1,80 (3 Kg Stainless Steel)

Number of heads



Bellhop H 850 mm


designed by Edward Barber and Jay Osgerby

100/240V power supply included. Ready for installation on rigid base. Each luminaire is equipped with a segment of 20 cm cable for connection inside the luminaire body. Suggested connection with 2 way terminal block 3 phases IP68, to be ordered separately.

F003B31A001 White
F003B31A006 Grey
F003B31A033 Anthracite
F003B31A030 Black

F003B31A018 Deep brown
F003B31A005 Stainless steel

DIMENSIONS




CERTIFICATIONS











Bellhop H 850 mm . Accessories

Electrical



F1205000

2 way terminal block 3 poles IP68

7-12 mm cables

Structural



F003Z010000

Base plate with bolt



Bellhop H 850 mm

designed by Edward Barber and Jay Osgerby

100/240V power supply included. Ready for installation on rigid base. Each luminaire is equipped with a segment of 20 cm cable for connection inside the luminaire body. Suggested connection with 2 way terminal block 3 phases IP68, to be ordered separately.

F003B31A001 White

F003B31A006 Grey

F003B31A033 Anthracite

F003B31A030 Black

F003B31A018 Deep brown

F003B31A005 Stainless steel

DIMENSIONS




CERTIFICATIONS













Bellhop H 850 mm . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED



Bellhop H 850 mm

designed by Edward Barber and Jay Osgerby

100/240V power supply included. Ready for installation on rigid base. Each luminaire is equipped with a segment of 20 cm cable for connection inside the luminaire body. Suggested connection with 2 way terminal block 3 phases IP68, to be ordered separately.

F003B31A001 White

F003B31A006 Grey


F003B31A033 Anthracite

F003B31A030 Black

F003B31A018 Deep brown

F003B31A005 Stainless steel

DIMENSIONS



CERTIFICATIONS









