FLOS

BELLHOP H 850 MM DIMMABLE 1-10V

85°

Beam angle
Mounting
Lamps description
Environment
Technical description

Floor Power LED: 8W - 816 lm ≠ FIXT 580 lm - 3000K/CRI 80 - 100-240V Outdoor Bollard version of the Bellhop Outdoor Collection for diffuse light. Made of extruded and die-cast aluminium or stainless steel, Bellhop is available in two heights for the bollard model and with different lumens and luminaire outputs as to comply with any outdoor setting and lighting scenario need.</

Bellhop H 850 mm Dimmable I-10V


designed by Edward Barber and Jay Osgerby

100/240 Ready fo

100/240V power supply included. Ready for installation on rigid base. Each luminaire is equipped with a segment of 20 cm cable for connection inside the luminaire body. Suggested connection with 2 way terminal block 3 phases IP68, to be ordered separately.




DIMENSIONS



CERTIFICATIONS





onic dimmable 1-10V

Transformer type
Transformer availability
Transformer mounting
Emergency
Voltage (V)

Electronic dimmable 1-10V Included Integral Without 100/240

PHYSICAL

ELECTRICAL

Aiming Weight (kg) Number of heads Fixed 1,80 (3 Kg Stainless Steel)



www.flos.com info@flos.it

FLOS

Bellhop H 850 mm Dimmable I-10V . Accessories

Electrical



F1205000

2 way terminal block 3 poles IP68 7-12 mm cables

Structural





Base plate with bolt




Bellhop H 850 mm Dimmable I-10V

designed by Edward Barber and Jay Osgerby

100/240V power supply included. Ready for installation on rigid base. Each luminaire is equipped with a segment of 20 cm cable for connection inside the luminaire body. Suggested connection with 2 way terminal block 3 phases IP68, to be ordered separately.




DIMENSIONS



CERTIFICATIONS





www.flos.com info@flos.it

FLOS

Bellhop H 850 mm Dimmable 1-10V . Lamps



Power LED

Lamp category: LED Socket: Special base Lamp type: Power LED




Bellhop H 850 mm Dimmable 1-10V

designed by Edward Barber and Jay Osgerby

100/240V power supply included. Ready for installation on rigid base. Each luminaire is equipped with a segment of 20 cm cable for connection inside the luminaire body. Suggested connection with 2 way terminal block 3 phases IP68, to be ordered separately.




DIMENSIONS



CERTIFICATIONS





www.flos.com info@flos.it