FLOS

LANDLORD GROUND Ø49 PWM DIMMABLE

Beam angle
Mounting
Lamps description
Environment
Technical description

14° Spot

Ground Power LED: 2,3W - 202 Im ≠ FIXT 130 Im - 4000K/CRI 80 - 24V Outdoor IP67 luminaries for ground recessed installation, powered 24V. Body in anodised, then resined aluminium, external ring in shot-peened stainless steel, encasing the entire control electronics. Head available in two sizes, ø47 mm, and ø64 mm, with frontal or grazing emission (one, two or four beams). Frontal emission version are available with spot or medium optic, and the ø64 version is also available with integrated non removable honeycomb, for maximum visual confort. To be installed in its installation box.

ELECTRICAL

Transformer type
Transformer availability
Transformer mounting
Emergency
Voltage (V)

Electronic dimmable Separate item Remote Without 24

PHYSICAL

Aiming	Fixed
Diameter (mm)	49
Weight (kg)	0,30
Number of heads	I






Landlord Ground Ø49 PWM Dimmable

designed by Piero Lissoni


24V remote power supply to be ordered separately. Necessary box for installation, to be ordered separately.


F004A41H005 Stainless steel

DIMENSIONS



CERTIFICATIONS





FLOS

Landlord Ground Ø49 PWM Dimmable . Accessories





Installation box




Landlord Ground Ø49 PWM Dimmable

designed by Piero Lissoni


24V remote power supply to be ordered separately. Necessary box for installation, to be ordered separately.




DIMENSIONS



CERTIFICATIONS







Landlord Ground Ø49 PWM Dimmable . Lamps



Power LED

Lamp category: LED Socket: Special base Lamp type: Power LED