

## LANDLORD GROUND Ø49

<b>Beam angle</b>	40° Medium
<b>Mounting</b>	Ground
<b>Lamps description</b>	Power LED: 2,3W - 202 lm ≠ FIXT 103 lm - 4000K/CRI 80 - 24V
<b>Environment</b>	Outdoor
<b>Technical description</b>	IP67 luminaries for ground recessed installation, powered 24V. Body in anodised, then resined aluminium, external ring in shot-peened stainless steel, encasing the entire control electronics. Head available in two sizes, Ø47 mm, and Ø64 mm, with frontal or grazing emission (one, two or four beams). Frontal emission version are available with spot or medium optic, and the Ø64 version is also available with integrated non removable honeycomb, for maximum visual confort. To be installed in its installation box.




### Landlord Ground Ø49

designed by Piero Lissoni

24V remote power supply to be ordered separately. Necessary box for installation, to be ordered separately.

● F004A42A005 Stainless steel

### DIMENSIONS



### ELECTRICAL



<b>Transformer type</b>	Electronic
<b>Transformer availability</b>	Separate item
<b>Transformer mounting</b>	Remote
<b>Emergency</b>	Without
<b>Voltage (V)</b>	24

### PHYSICAL

<b>Aiming</b>	Fixed
<b>Diameter (mm)</b>	49
<b>Weight (kg)</b>	0,30
<b>Number of heads</b>	1





### CERTIFICATIONS



## Landlord Ground Ø49 .Accessories

### Mounting



F004Z0J0000


Installation box



### Landlord Ground Ø49


designed by Piero Lissoni

24V remote power supply to be ordered separately. Necessary box for installation, to be ordered separately.



F004A42A005 Stainless steel

### DIMENSIONS



## Landlord Ground Ø49 . Lamps



### Power LED

#### Lamp category:

LED

#### Socket:

Special base

#### Lamp type:

Power LED

### CERTIFICATIONS

