

LANDLORD GROUND Ø64 I BEAM

Beam angle	14°
Mounting	Ground
Lamps description	Power LED: 3,4W - 251 lm ≠ FIXT I lm - 2700K/CRI 80 - 24V
Environment	Outdoor
Technical description	IP67 luminaries for ground recessed installation, powered 24V. Body in anodised, then resined aluminium, external ring in shot-peened stainless steel, encasing the entire control electronics. Head available in two sizes, ø47 mm, and ø64 mm, with frontal or grazing emission (one, two or four beams). Frontal emission version are available with spot or medium optic, and the ø64 version is also available with integrated non removable honeycomb, for maximum visual confort. To be installed in its installation box.




Landlord Ground Ø64 I Beam designed by Piero Lissoni

24V remote power supply to be ordered separately. Necessary box for installation, to be ordered separately.

● F004B23A005 Stainless steel

DIMENSIONS



ELECTRICAL

Transformer type	Electronic
Transformer availability	Separate item
Transformer mounting	Remote
Emergency	Without
Voltage (V)	24

PHYSICAL

Aiming	Fixed
Diameter (mm)	64
Weight (kg)	0,35
Number of heads	1




CERTIFICATIONS



Landlord Ground Ø64 I Beam .Accessories

Mounting



○ F004Z0K0000

Installation box




Landlord Ground Ø64 I Beam

designed by Piero Lissoni

24V remote power supply to be ordered separately. Necessary box for installation, to be ordered separately.

● F004B23A005 Stainless steel

DIMENSIONS



CERTIFICATIONS



Landlord Ground Ø64 I Beam . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED