

#### LANDLORD GROUND Ø64 2 BEAM PWM DIMMABLE

45° Beam angle **Mounting** Ground

Power LED: 3,4W - 251 lm ≠ FIXT 22 lm - 2700K/CRI 80 - 24V Lamps description

**Environment** Outdoor

IP67 luminaries for ground recessed installation, powered 24V. **Technical description** 

Body in anodised, then resined aluminium, external ring in shot-peened stainless steel, encasing the entire control electronics. Head available in two sizes, ø47 mm, and ø64 mm, with frontal or grazing emission (one, two or four beams). Frontal emission version are available with spot or medium optic, and the ø64 version is also available with integrated non removable honeycomb, for maximum visual

confort. To be installed in its installation box.



Transformer type Electronic dimmable Transformer availability Separate item

**Transformer mounting** Remote **Emergency** Without Voltage (V) 24

**PHYSICAL** 

**Aiming** Fixed Diameter (mm) 0,35 Weight (kg) **Number of heads** ı





#### Landlord Ground Ø64 2 Beam **PWM Dimmable**

designed by Piero Lissoni

24V remote power supply to be ordered separately. Necessary box for installation, to be ordered separately.



F004B24H005 Stainless steel

#### **DIMENSIONS**



Ø64



## **CERTIFICATIONS**









67



# Landlord Ground Ø64 2 Beam PWM Dimmable . Accessories

## **Mounting**



F004Z0K0000

Installation box

# Landlord Ground Ø64 2 Beam PWM Dimmable . Lamps



**Power LED** 

Lamp category:

LED

Socket:

Special base

Lamp type: Power LED



# Landlord Ground Ø64 2 Beam PWM Dimmable

designed by Piero Lissoni

24V remote power supply to be ordered separately. Necessary box for installation, to be ordered separately.



F004B24H005 Stainless steel

# **DIMENSIONS**



Ø64



## **CERTIFICATIONS**









67