

LANDLORD GROUND Ø64 2 BEAM

45° Beam angle **Mounting** Ground

Power LED: 3,4W - 260 lm ≠ FIXT 23 lm - 3000K/CRI 80 - 24V Lamps description

Environment Outdoor

IP67 luminaries for ground recessed installation, powered 24V. **Technical description**

Body in anodised, then resined aluminium, external ring in shot-peened stainless steel, encasing the entire control electronics. Head available in two sizes, ø47 mm, and ø64 mm, with frontal or grazing emission (one, two or four beams). Frontal emission version are available with spot or medium optic, and the ø64 version is also available with integrated non removable honeycomb, for maximum visual

confort. To be installed in its installation box.



Transformer type Electronic Transformer availability Separate item **Transformer mounting** Remote **Emergency** Without Voltage (V) 24

PHYSICAL

Aiming Fixed Diameter (mm) 64 0,35 Weight (kg) **Number of heads** ı





Landlord Ground Ø64 2 Beam

designed by Piero Lissoni

24V remote power supply to be ordered separately. Necessary box for installation, to be ordered separately.



F004B34A005 Stainless steel

DIMENSIONS



Ø64



CERTIFICATIONS













Landlord Ground Ø64 2 Beam . Accessories

Mounting



F004Z0K0000

Installation box

Landlord Ground Ø64 2 Beam . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED



Landlord Ground Ø64 2 Beam

designed by Piero Lissoni

24V remote power supply to be ordered separately. Necessary box for installation, to be ordered separately.



F004B34A005 Stainless steel

DIMENSIONS



Ø64



CERTIFICATIONS







