# FLOS

### LANDLORD GROUND Ø64 4 BEAM

Beam angle	41°
Mounting	Ground
Lamps description	Power LED: 3,4W - 270 Im ≠ FIXT 48 Im - 4000K/CRI 80 - 24V
Environment	Outdoor
Technical description	IP67 luminaries for ground recessed installation, powered 24V. Body in anodised, then resined aluminium, external ring in shot-peened stainless steel, encasing the entire control electronics. Head available in two sizes, ø47 mm, and ø64 mm,

Electronic Separate item

Remote

Without 24

with frontal or grazing emission (one, two or four beams). Frontal emission version are available with spot or medium optic, and the ø64 version is also available with integrated non removable honeycomb, for maximum visual confort. To be installed in its installation box.

## ELECTRICAL

Transformer type
Transformer availability
Transformer mounting
Emergency
Voltage (V)

#### PHYSICAL

Aiming	Fixed
Diameter (mm)	64
Weight (kg)	0,35
Number of heads	I





### Landlord Ground Ø64 4 Beam

designed by Piero Lissoni

24V remote power supply to be ordered separately. Necessary box for installation, to be ordered separately.

### F004B45A005 Stainless steel


#### DIMENSIONS





## CERTIFICATIONS





# FLOS

## Landlord Ground Ø64 4 Beam . Accessories

## Mounting





Installation box

# Landlord Ground Ø64 4 Beam . Lamps



Power LED


Lamp category:
LED
Socket:
Special base
Lamp type:
Power LED




## Landlord Ground Ø64 4 Beam

designed by Piero Lissoni

24V remote power supply to be ordered separately. Necessary box for installation, to be ordered separately.



DIMENSIONS



# CERTIFICATIONS

