FLOS

LANDLORD SPOT Ø50 PWM DIMMABLE

Beam angle26° MediumMountingGround

Lamps description Power LED: 7,2W - 689 lm ≠ FIXT 457 lm - 3000K/CRI 80 - 24V

Environment Outdoor

Technical description IP65 projector for external use made of turned aluminium

body and powered at 24V, and available in 2700K, 3000K and 4000K colour temperatures. With reference to the horizontal axis, the spot can be oriented up to 30° down and up to 90° up. Landlord Spots are available in two sizes, ø40 and ø50 head, both equipped with desmontable front ferrule, in order to install flood lens or up to two honeycombs for maximum visual confort. Landlord Spots can be installed on solid ground spikes, with the possibility of an optional picket, on wall base, or on the innovative tree belt, designed to fix the luminaries

directly on tree branches.



Transformer type Electronic dimmable
Transformer availability Separate item
Transformer mounting Remote
Emergency Without
Voltage (V) 24

PHYSICAL

Aiming Adjustable
Weight (kg) 0,35
Number of heads I





Landlord Spot Ø50 PWM Dimmable


designed by Piero Lissoni

Spot orientable head for installation on ground poles or on wall base. Poles and base to be ordered as separated accessories. Heads are equipped with a dismountable ferrule, to insert flood lens or up to two honeycombs, (to be ordered as separate accessories). 24V remote power supply to be ordered separately. Each head comes with a segment of 2m outgoing cable and a wiring kit.

F004E32A001 White
F004E32A006 Grey
F004E32A033 Anthracite
F004E32A030 Black
F004E32A018 Deep brown
F004G32A070 Óxido natural
F004G32A071 Óxido negro

F004G32A072 Green Product with Pole

DIMENSIONS



CERTIFICATIONS










IP 66



FLOS

Landlord Spot Ø50 PWM Dimmable . Accessories

Optical





F004Z0H0000

Flood lens

F004Z0L0000

Honeycomb

designed by Piero Lissoni

F004E32A001 White F004E32A006 Grey

Spot orientable head for installation on ground poles or on wall base. Poles and base to be ordered as separated accessories. Heads are equipped with a dismountable ferrule, to insert flood lens or up to two honeycombs, (to be ordered as separate accessories). 24V remote power supply to be ordered separately. Each head comes with a segment of 2m outgoing cable and a wiring kit.

Landlord Spot Ø50 PWM Dimmable

Mounting



Ø75 022



F004Z070000

Tree strap

Accessory for spot installation directly on three branch, from ø30 mm up to ø100mm.

F004Z060000

Earth stick

To be mounted on poles with base.

F004Z040001

F004Z040006

F004Z040033

F004Z040030

F004Z040018

F004Z0A0070

F004Z0A0071


F00.470.4.007

F004Z0A0072

Wall base

F004E32A033 Anthracite F004E32A030 Black F004E32A018 Deep brown F004G32A070 Óxido natural F004G32A071 Óxido negro F004G32A072 Green Product with Pole

DIMENSIONS



CERTIFICATIONS










IP 66



FLOS

Landlord Spot Ø50 PWM Dimmable . Accessories





F004Z030006

F004Z030033

F004Z030030

F004Z030018

F004Z0F0070

F004Z0F0071

F004Z0F0072

Pole with base H 900 mm

Ready for installation on rigid base. For ground installation, complete with earth stick, to be ordered as separated item.

Landlord Spot Ø50 PWM Dimmable . Lamps



F004Z020001

F004Z020006

F004Z020033

F004Z020030

F004Z020018

F004Z0E0070

F004Z0E0071

F004Z0E0072

Pole with base H 600 mm

Ready for installation on rigid base. For ground installation, complete with earth stick, to be ordered as separated item.



F004Z010001

F004Z010006

F004Z010033

F004Z010030

F004Z010018

F004Z0D0070

F004Z0D0071

F004Z0D0072

Pole with base H 300 mm

Ready for installation on rigid base. For ground installation, complete with earth stick, to be ordered as separated item.



Landlord Spot Ø50 PWM Dimmable

designed by Piero Lissoni

Spot orientable head for installation on ground poles or on wall base. Poles and base to be ordered as separated accessories. Heads are equipped with a dismountable ferrule, to insert flood lens or up to two honeycombs, (to be ordered as separate accessories). 24V remote power supply to be ordered separately. Each head comes with a segment of 2m outgoing cable and a wiring kit.

F004E32A001 White

F004E32A006 Grey

F004E32A033 Anthracite

F004E32A030 Black

F004E32A018 Deep brown

F004G32A070 Óxido natural

F004G32A071 Óxido negro

F004G32A072 Green

Product with Pole

DIMENSIONS



Power LED

Lamp category:


LED

Socket:

Special base

Lamp type:

Power LED



CERTIFICATIONS











