

#### **CLIMBER UP&DOWN - 175**

Beam angle 10°

**Lamps description** Power Led: 21W - 2x864 lm ≠ \*FIXT 2x739 lm - 2700K/CRI

80 - 220-240V (\*FIXT Im = Spot Optic)

**Environment** Indoor, Outdoor

**Notes** We recommend using a connection system with a degree of

protection greater than or equal to the degree of protection

of the luminaire

**Technical description** Bi-emission and mono-emission versions pointing

downwards. Aluminum die-cast body EN AB-47 100, low copper content with asymmetrical optics housing: the optics in the lower part is retracted and protected by a shutter to restrict annoying glare and maximize visual comfort. In the biemission version, the glass of the closure of the upper optics is flush with the edge of the light in order to prevent water deposits. The micro-texturized glass diffusers are glued to ensure water resistance and textured to ensure a uniform light beam generated by each single LED, maintaining excellent luminous efficiency. High-resistance coating: after a sandblasting treatment of all components to make the surface porous and ensure a greater adhesion of the paint, the external coating is applied with a double layer with epoxy powders according to the QUALICOAT standard. The first layer of epoxy powder gives chemical and mechanical resistance, the second finishing layer of polyester powder ensures resistance to UV rays and atmospheric agents. The painted surfaces are treated with alkaline and acidic washes, then rinsed with demineralized water, subjected to a chemical

conversion treatment to protect against oxidation.

### **ELECTRICAL**

Transformer type Electronic
Transformer availability Included
Transformer mounting Integral
Emergency Without
Voltage (V) 110/240

### **PHYSICAL**

IK rating04AimingFixedWeight (kg)2,20Number of headsI




#### Climber Up&Down - 175

designed by Piero Lissoni

Luminaire for outdoor use for installation on the wall with LED light source. Integrated 110/240V power source. Supplied with an 80 mm section of outgoing neoprene cable. Dimmable version on request.

F1146001 White
F1146006 Grey
F1146033 Anthracite
F1146030 Black
F1146018 Deep brown

### **DIMENSIONS**



### **CERTIFICATIONS**


















# Climber Up&Down - 175 . Lamps



## **Power LED**

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




## Climber Up&Down - 175

designed by Piero Lissoni

Luminaire for outdoor use for installation on the wall with LED light source. Integrated 110/240V power source. Supplied with an 80 mm section of outgoing neoprene cable. Dimmable version on request.

| F1146001 | White      |
|----------|------------|
| F1146006 | Grey       |
| F1146033 | Anthracite |
| F1146030 | Black      |
| F1146018 | Deep brown |

## **DIMENSIONS**



## **CERTIFICATIONS**











