

FLOS

MINIKELVIN WALL FLEX

Number of heads	1
Mounting	Wall surface
Lamps description	Top LED 4W 216 lm 3000K CRI 85
Luminaire luminous flux	See reference number
Environment	Indoor

OPTICAL

Aiming	Adjustable
Light distribution symmetry	Symmetric
Beam angle	111°

ELECTRICAL

Transformer availability	Included
Transformer mounting	On plug
Transformer type	Electronic dimmable
Emergency	Without
Insulation class	Class III

PHYSICAL


Construction material	Aluminium
Weight (kg)	0,38



Minikelvin Wall Flex
designed by Antonio Citterio

Diffuse illumination lighting device for wall mounting. Wall attachment in die-cast aluminium. The adaptor is on the plug and the useful cable length is 200 cm. ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% - 50% - 0%).

● F4185009 - 96lm	White
● F4185057 - 96lm	Chrome
● F4185030 - 96lm	Black



CERTIFICATIONS



Minikelvin Wall Flex . Lamps



Top LED

Lamp category:
LED

Socket:
Special base


Lamp type:
Top LED



Minikelvin Wall Flex
designed by Antonio Citterio

Diffuse illumination lighting device for wall mounting. Wall attachment in die-cast aluminium. The adaptor is on the plug and the useful cable length is 200 cm. ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% - 50% - 0%).

	F4185009 - 96lm	White
	F4185057 - 96lm	Chrome
	F4185030 - 96lm	Black



CERTIFICATIONS

