

## OUTGRAZE 48 L I 200 MM

<b>Beam angle</b>	44°
<b>Mounting</b>	Ceiling surface, Wall surface
<b>Lamps description</b>	Power Led: 32W - 3360 lm ≠ *FIXT 2580 lm - 4000K/CRI 80 - 220-240V (*FIXT lm = Medium Optic)
<b>Environment</b>	Indoor, Outdoor
<b>Notes</b>	We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

<b>Technical description</b>	Central body in extruded aluminum, end cap in die-cast aluminum. Optics made with constant pitch between the lenses to offer a homogeneous luminous flux even in case of multiple lamps installed in a continuous line. High resistance external coating applied with a double layer of epoxy powders in accordance with the QUALICOAT standard. The first layer of epoxy powder gives chemical and mechanical resistance, the second finishing layer of polyester powder ensures resistance to UV rays and atmospheric agents. The painted surfaces are treated with alkaline and acidic washes, then rinsed with demineralized water, subjected to a chemical conversion treatment to protect against oxidation. Diffuser in extra clear transparent glass, screen-printed and glued to ensure a watertight seal. The installation of the product requires use of steel brackets, to be ordered separately. Luminaire provided with a length of approximately 1500 mm of outgoing neoprene cable on one side. On request it is possible to provide luminaires with loop-through connection for multiple installation with continuity of line.
------------------------------	---

### ELECTRICAL

<b>Transformer type</b>	Electronic
<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Integral
<b>Emergency</b>	Without
<b>Voltage (V)</b>	220/240

### PHYSICAL

<b>IK rating</b>	06
<b>Aiming</b>	Fixed
<b>Weight (kg)</b>	4,31
<b>Number of heads</b>	1




### Outgraze 48 L I 200 mm

designed by FLOS Outdoor



Luminaire for outdoor use for installation on the wall or ceiling with LED light source. Integrated 220/240V power source. Installation brackets, to be ordered separately. Dimmable version on request.

● F4237001	White
● F4237006	Grey
● F4237033	Anthracite
● F4237030	Black
● F4237018	Deep brown

### DIMENSIONS



### CERTIFICATIONS





## Outgraze 48 L 1200 mm

designed by FLOS Outdoor

Luminaire for outdoor use for installation on the wall or ceiling with LED light source. Integrated 220/240V power source. Installation brackets, to be ordered separately. Dimmable version on request.

F4237001	White
F4237006	Grey
F4237033	Anthracite
F4237030	Black
F4237018	Deep brown

## Outgraze 48 L 1200 mm .Accessories

### Structural




F4204001
F4204006
F4204033
F4204030
F4204018

One pair of long rods L 200 mm.


F4203001
F4203006
F4203033
F4203030
F4203018

One pair of short rods L 80 mm.

## DIMENSIONS



## CERTIFICATIONS



## Outgraze 48 L 1200 mm .Accessories

### Electrical



F1206000

**3/4 way terminal block 3 poles IP68**

7-12 mm cables



F1205000

**2 way terminal block 3 poles IP68**

7-12 mm cables

## Outgraze 48 L 1200 mm . Lamps



### Power LED

**Lamp category:**  
LED

**Socket:**  
Special base

**Lamp type:**  
Power LED




### Outgraze 48 L 1200 mm

designed by FLOS Outdoor

Luminaire for outdoor use for installation on the wall or ceiling with LED light source. Integrated 220/240V power source. Installation brackets, to be ordered separately. Dimmable version on request.

	F4237001	White
	F4237006	Grey
	F4237033	Anthracite
	F4237030	Black
	F4237018	Deep brown

### DIMENSIONS



### CERTIFICATIONS

