

## OUTGRAZE 35 L 1200 MM

<b>Beam angle</b>	31°
<b>Mounting</b>	Ceiling surface, Wall surface
<b>Lamps description</b>	Power Led: 30W - 2600 lm ≠ *FIXT 1931 lm - 3000K/CRI 80 - 48V (*FIXT lm = Medium Optic)
<b>Environment</b>	Indoor, Outdoor
<b>Notes</b>	We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

<b>Technical description</b>	Central body in extruded aluminum, end cap in die-cast aluminum. Optics made with constant pitch between the lenses to offer a homogeneous luminous flux even in case of multiple lamps installed in a continuous line. High resistance external coating applied with a double layer of epoxy powders in accordance with the QUALICOAT standard. The first layer of epoxy powder gives chemical and mechanical resistance, the second finishing layer of polyester powder ensures resistance to UV rays and atmospheric agents. The painted surfaces are treated with alkaline and acidic washes, then rinsed with demineralized water, subjected to a chemical conversion treatment to protect against oxidation. Diffuser in extra clear transparent glass, screen-printed and glued to ensure a watertight seal. The installation of the product requires use of steel brackets, to be ordered separately. Luminaire provided with a length of approximately 1500 mm of outgoing neoprene cable on one side. On request it is possible to provide luminaires with loop-through connection for multiple installation with continuity of line.
------------------------------	---

### ELECTRICAL

<b>Transformer type</b>	Electronic
<b>Transformer availability</b>	Separate item
<b>Transformer mounting</b>	Remote
<b>Emergency</b>	Without
<b>Voltage (V)</b>	48

### PHYSICAL

<b>IK rating</b>	07
<b>Aiming</b>	Fixed
<b>Weight (kg)</b>	2,90
<b>Number of heads</b>	1




### Outgraze 35 L 1200 mm

designed by FLOS Outdoor



Luminaire for outdoor use for installation on the wall or ceiling with LED light source. 48V power source not included. Driver for remote installation and installation brackets to be ordered separately. Dimmable PWM luminaires.

● F4254001	White
● F4254006	Grey
● F4254033	Anthracite
● F4254030	Black
● F4254018	Deep brown

### DIMENSIONS



### CERTIFICATIONS





## Outgraze 35 L 1200 mm

designed by FLOS Outdoor

Luminaire for outdoor use for installation on the wall or ceiling with LED light source. 48V power source not included. Driver for remote installation and installation brackets to be ordered separately. Dimmable PWM luminaires.

F4254001	White
F4254006	Grey
F4254033	Anthracite
F4254030	Black
F4254018	Deep brown

## Outgraze 35 L 1200 mm .Accessories

### Structural




F4254001
F4254006
F4254033
F4254030
F4254018

One pair of long rods L 200 mm.


F4253001
F4253006
F4253033
F4253030
F4253018

One pair of short rods L 80 mm.

## DIMENSIONS




## CERTIFICATIONS



## Outgraze 35 L 1200 mm .Accessories

### Power Supply



RF25746

#### Power supply 240W

Power supply 48V 240W /  
110-240V single output DIN  
RAIL.



RF25753

#### Power supply 60W

Power supply 48V 60W /  
110-240V IP67 Class I selv  
eq.




### Outgraze 35 L 1200 mm

designed by FLOS Outdoor

Luminaire for outdoor use for  
installation on the wall or ceiling with  
LED light source. 48V power source  
not included. Driver for remote  
installation and installation brackets to  
be ordered separately. Dimmable  
PWM luminaires.

●	F4254001	White
●	F4254006	Grey
●	F4254033	Anthracite
●	F4254030	Black
●	F4254018	Deep brown

### DIMENSIONS



### CERTIFICATIONS



### Electrical



FI206000

#### 3/4 way terminal block 3 poles IP68


7-12 mm cables



FI205000

#### 2 way terminal block 3 poles IP68

7-12 mm cables



## Outgraze 35 L 1200 mm . Lamps



### Power LED

**Lamp category:**  
LED

**Socket:**  
Special base

**Lamp type:**  
Power LED




### Outgraze 35 L 1200 mm

designed by FLOS Outdoor

Luminaire for outdoor use for installation on the wall or ceiling with LED light source. 48V power source not included. Driver for remote installation and installation brackets to be ordered separately. Dimmable PWM luminaires.

● F4254001	White
● F4254006	Grey
● F4254033	Anthracite
● F4254030	Black
● F4254018	Deep brown

### DIMENSIONS



### CERTIFICATIONS

