# FLOS

#### MY WAY 110X100

Beam angle	74°
Mounting	Wall surface
Lamps description	Mid-Power Led: 5W - 514 lm ≠ FIXT 221 lm - 4000K/CRI 80 - 100-240V
Environment	Indoor, Outdoor
Notes	We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.
Technical description	Aluminum die-cast body EN AB-47100 (low copper content). High-resistance coating: after a sandblasting treatment of all components to make the surface porous and ensure a greater adhesion of the paint, the external coating is applied with a double layer with epoxy powders according to the QUALICOAT standard. The first layer of epoxy powder gives chemical and mechanical resistance, the second finishing layer of polyester powder ensures resistance to UV rays and atmospheric agents. The painted surfaces are treated with alkaline and acidic washes, then rinsed with demineralized water, subjected to a chemical conversion treatment to protect against oxidation. Frosted polycarbonate diffuser, UV- stabilised, glued to the head of the product to ensure a watertight seal.



### My Way 110x100

designed by Piero Lissoni

Luminaire for outdoor use for built-in installation on the wall with LED light source. Integrated 110/240V power source. Supplied with a 120 mm section of outgoing neoprene cable and IP67 cable connection system.

# ELECTRICAL


Transformer type	Electronic
Transformer availability	Included
Transformer mounting	Integral
Emergency	Without
Voltage (V)	100/240

Fixed 0,52 I


#### PHYSICAL

Aiming	
Weight (kg)	
Number of heads	

F4352001	White	
F4352006	Grey	
F4352033	Anthracite	
<b>F</b> 4352030	Black	
F4352018	Deep brown	
DIMENSIONS		







# FLOS



### My Way 110x100 . Accessories

Electrical






2 way terminal block 3 poles IP68 7-12 mm cables




#### My Way 110x100


designed by Piero Lissoni


Luminaire for outdoor use for built-in installation on the wall with LED light source. Integrated 110/240V power source. Supplied with a 120 mm section of outgoing neoprene cable and IP67 cable connection system.



DIMENSIONS







# FLOS

# My Way 110x100 . Accessories

#### Mounting



122 <u>70</u> EE



**Remote Housing** 

## My Way 110x100 . Lamps



#### Mid-Power LED


Lamp category: LED Socket: Special base Lamp type: Power LED



#### My Way 110x100

designed by Piero Lissoni

Luminaire for outdoor use for built-in installation on the wall with LED light source. Integrated 110/240V power source. Supplied with a 120 mm section of outgoing neoprene cable and IP67 cable connection system.



DIMENSIONS

