

A-ROUND 240

Beam angle 25° **Mounting** Ground

Lamps description Power Led: 21W - 2200 lm - 4000K/CRI 80 - 220-240V

Environment Outdoor

Notes We recommend using a connection system with a degree of

protection greater than or equal to the degree of protection

of the luminaire.

Technical description External body made of stainless steel AISI 316L treated with

the PVD process (Physical Vapour Deposition). Thanks to this innovative treatment, after the polishing or brushing process, according to the finishing choice, the surfaces of A-Round are coated with a thin film of metals such as zirconium and titanium which, combining with the steel at the molecular level, increase the resistance to both mechanical and to atmospheric agents, permitting the execution of elegant and durable finishings. The body of the luminaire is made of diecast aluminum EN AB-47100 with low copper content, coated

with two layers of paint with high resistance to corrosion. High-strength tempered clear glass, screen-pri

corrosion. High-strength tempered clear glass, screen-printed to reduce glare. Driver for remote installation included, provided with M12 quick connector for watertight

provided with M12 quick connector for watertight coupling. Installation requires a housing for flush mounting, to be ordered separately. It is necessary to provide an adequate level of gravel (> 300 mm) or a drain system to ensure drainage and avoid water stagnation. To ensure the sealing of the cable gland it is necessary to use flexible electric cables

suitable for use in outdoor environments.



Transformer type Electronic
Transformer availability Included
Transformer mounting Integral
Emergency Without
Voltage (V) 220/240

PHYSICAL

Aiming Adjustable
Diameter (mm) 240
Number of heads I




A-Round 240

designed by Piero Lissoni

Ground-recessed luminaire for outdoor use, walkable and trafficable, available in three sizes, with adjustable optics in various configurations. Integrated 220/240V power source. Remote housing required, to be ordered separately. Dimmable version on request.

F4586015 Polished copper
F4586046 Brushed bronze
F4586044 Brushed gold
F4586056 Brushed steel

DIMENSIONS



















A-Round 240 . Accessories

Optical





F4556000

Honeycomb. 4 units Kit

Flood lens. 4 units Kit

F4559000


A-Round 240

designed by Piero Lissoni

Ground-recessed luminaire for outdoor use, walkable and trafficable, available in three sizes, with adjustable optics in various configurations. Integrated 220/240V power source. Remote housing required, to be ordered separately. Dimmable version on request.

F4586015 Polished copper
F4586046 Brushed bronze
F4586044 Brushed gold
F4586056 Brushed steel

DIMENSIONS













A-Round 240 . Accessories

Mounting



F4598000

Remote Housing

Electrical





F1206000

3/4 way terminal block 3 poles IP68

7-12 mm cables

F1205000

2 way terminal block 3 poles IP68

7-12 mm cables




A-Round 240

designed by Piero Lissoni

Ground-recessed luminaire for outdoor use, walkable and trafficable, available in three sizes, with adjustable optics in various configurations. Integrated 220/240V power source. Remote housing required, to be ordered separately. Dimmable version on request.

F4586015 Polished copper
F4586046 Brushed bronze
F4586044 Brushed gold
F4586056 Brushed steel

DIMENSIONS













A-Round 240 . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED



A-Round 240

designed by Piero Lissoni

Ground-recessed luminaire for outdoor use, walkable and trafficable, available in three sizes, with adjustable optics in various configurations. Integrated 220/240V power source. Remote housing required, to be ordered separately. Dimmable version on request.

F4586015 Polished copper
F4586046 Brushed bronze
F4586044 Brushed gold
F4586056 Brushed steel

DIMENSIONS

