

A-ROUND 315

| | |
|--------------------------|--|
| Beam angle | 10° |
| Mounting | Ground |
| Lamps description | Power Led: 42W - 3978 lm - 3000K/CRI 80 - 220-240V |
| Environment | Outdoor |
| Notes | We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire. |


| | |
|------------------------------|---|
| Technical description | External body made of stainless steel AISI 316L treated with the PVD process (Physical Vapour Deposition). Thanks to this innovative treatment, after the polishing or brushing process, according to the finishing choice, the surfaces of A-Round are coated with a thin film of metals such as zirconium and titanium which, combining with the steel at the molecular level, increase the resistance to both mechanical and to atmospheric agents, permitting the execution of elegant and durable finishings. The body of the luminaire is made of die-cast aluminum EN AB-47100 with low copper content, coated with two layers of paint with high resistance to corrosion. High-strength tempered clear glass, screen-printed to reduce glare. Driver for remote installation included, provided with M12 quick connector for watertight coupling. Installation requires a housing for flush mounting, to be ordered separately. It is necessary to provide an adequate level of gravel (> 300 mm) or a drain system to ensure drainage and avoid water stagnation. To ensure the sealing of the cable gland it is necessary to use flexible electric cables suitable for use in outdoor environments. |
|------------------------------|---|

ELECTRICAL

| | |
|---------------------------------|------------|
| Transformer type | Electronic |
| Transformer availability | Included |
| Transformer mounting | Integral |
| Emergency | Without |
| Voltage (V) | 220/240 |

PHYSICAL

| | |
|------------------------|------------|
| Aiming | Adjustable |
| Diameter (mm) | 315 |
| Number of heads | 1 |




A-Round 315

designed by Piero Lissoni

Ground-recessed luminaire for outdoor use, walkable and trafficable, available in three sizes, with adjustable optics in various configurations. Integrated 220/240V power source. Remote housing required, to be ordered separately. Dimmable version on request.


| | | |
|--|----------|-----------------|
| | F4591015 | Polished copper |
| | F4591046 | Brushed bronze |
| | F4591044 | Brushed gold |
| | F4591056 | Brushed steel |

DIMENSIONS



CERTIFICATIONS






A-Round 315

designed by Piero Lissoni

Ground-recessed luminaire for outdoor use, walkable and trafficable, available in three sizes, with adjustable optics in various configurations. Integrated 220/240V power source. Remote housing required, to be ordered separately. Dimmable version on request.

| | | |
|--|----------|-----------------|
| | F4591015 | Polished copper |
| | F4591046 | Brushed bronze |
| | F4591044 | Brushed gold |
| | F4591056 | Brushed steel |

DIMENSIONS



CERTIFICATIONS



A-Round 315 .Accessories

Optical



F4557000


Honeycomb. 6 units Kit

F4560000

Flood lens. 6 units Kit


A-Round 315 .Accessories

Mounting



F4599000

Remote Housing




A-Round 315

designed by Piero Lissoni

Ground-recessed luminaire for outdoor use, walkable and trafficable, available in three sizes, with adjustable optics in various configurations. Integrated 220/240V power source. Remote housing required, to be ordered separately. Dimmable version on request.

-  F4591015 Polished copper
-  F4591046 Brushed bronze
-  F4591044 Brushed gold
-  F4591056 Brushed steel

DIMENSIONS



CERTIFICATIONS



Electrical



F1206000

3/4 way terminal block 3 poles IP68

7-12 mm cables



F1205000

2 way terminal block 3 poles IP68

7-12 mm cables

A-Round 315 . Lamps




Power LED

Lamp category:
LED

Socket:
Special base

Lamp type:
Power LED




A-Round 315

designed by Piero Lissoni

Ground-recessed luminaire for outdoor use, walkable and trafficable, available in three sizes, with adjustable optics in various configurations. Integrated 220/240V power source. Remote housing required, to be ordered separately. Dimmable version on request.

| | | |
|--|----------|-----------------|
| | F4591015 | Polished copper |
| | F4591046 | Brushed bronze |
| | F4591044 | Brushed gold |
| | F4591056 | Brushed steel |

DIMENSIONS



CERTIFICATIONS

