


Ray Floor 2

by Rodolfo Dordoni, 2006



Floor lamp providing diffused lighting. Steel tube structure, welded, brushed and chrome-plated. Diffuser support in die-cast, polished and chrome-plated Zamak alloy. Injection-molded PA6 (nylon) lamp-cover. Color: white. Injection-molded PC (polycarbonate) inner diffuser. Color: 3% opal. Injection-molded elastic PVC (polyvinylchloride) feet. Lathe-shaped aluminum diffusers, painted white on the inside, and shiny white or black on the outside or gray-colored, blown and overlaid glass with glossy external finish. On the cable there is the electronic dimmer which allows the regulation of light brightness.







Mounting Floor
Environment Indoor

Finish White, Glass, Black
Weight 6.2 (met) - 9.2 (glass) Kg

Light sources 1 x HSGS E27 205W 3000K Halolux Ceram.Eco

available 4200lm - RF19973

1 x LED E27 A65 21W 3000K 2452lm - RF26998

Emergency Without

Switching On the cable there is the electronic dimmer

which allows the regulation of light brightness

with a dial.

Voltage 220-240V Power MAX 250W

Battery No Supply included Yes

Cord Length 1900 mm

Materials Aluminum, Glass, Steel

Colors F5921030 - Black

F5921009 - White