## **KTribe Floor 1**

by Philippe Starck , 2007

Floor lamp providing diffused lighting; a switch located near the diffuser allows for 4-level light adjustment via a "remote" dimmer positioned on the power cord near the plug. Base and rod support in die-cast, polished and chrome-plated Zamak alloy. Rod, arm support, arm and diffuser support in polished aluminum tube. Molded steel counterweight with galvanized finish. Injection-molded PC (polycarbonate) inner diffuser opal color. Outer diffusers in transparent or fumèe PMMA (polymethylmethacrylate) and silver or bronze on the inner surface, by vacuum aluminum coating. Injection-molded PC (polycarbonate) upper ring, completely transparent, or transparent brown for the outer bronze diffuser.

Mounting	Floor
Environment	Indoor
Finish	Aluminized bronze, Aluminized silver, Fabric, Fumée, Transparent
Weight	4.3 Kg
Light sources available	1 x HSGS E27 70W 2800K 1180lm - RF20405 1 x LED E27 8W 2700K 740lm - RF25323 1 x LED E27 8W 3000K 740lm - RF25317
Emergency	Without
Switching	On the cable there is the electronic dimmer which allows the step regulation of light brightness with a push button hidden under the diffuser stem.
Voltage	220-240V
Power	MAX 100W
Battery	No
Supply includ	ed Yes
Cord Length	1500 mm
Materials	Aluminum, Fabric, Polycarbonate, Polymethylmethacrylate
Colors	<ul> <li>F62650 - Fabric</li> <li>F6265004 - Aluminized silver</li> <li>F6265046 - Aluminized bronze</li> <li>F6265000 - Transparent</li> <li>F6265030 - Fumée</li> </ul>







