

## WALL SYSTEM MINIKELVIN FLEX POWER SUPPLY INTEGRATED

Number of heads	1
Mounting	Wall surface
Lamps description	Top LED 4W 216 lm 3000K CRI 85
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor

### OPTICAL

Aiming	Adjustable
Light distribution symmetry	Symmetric
Beam angle	111°

### ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic dimmable
Emergency	Without
Insulation class	Class III

### PHYSICAL

Construction material	Aluminium
Weight (kg)	0,40




### Wall System Minikelvin Flex Power Supply Integrated

designed by Antonio Citterio

Diffuse illumination lighting device for installation flush with the wall with integrated driver and with round ornamental (ø125). ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% - 50% - 0%).

● F9463009 - 96lm	White
● F9463057 - 96lm	Chrome
● F9463030 - 96lm	Black



### CERTIFICATIONS



## Wall System Minikelvin Flex Power Supply Integrated . Accessories

### Mounting



80.8006

#### 3-module flush mounted box for Pladur

3-module flush mounted box for Pladur, measuring 110.2x68.8x53.7 mm.



80.8067

#### 3-module flush mounted box for masonry

3-module flush mounted box for masonry, measuring 119x80x50 mm.



#### Wall System Minikelvin Flex Power Supply Integrated

designed by Antonio Citterio

Diffuse illumination lighting device for installation flush with the wall with integrated driver and with round ornamental (ø125). ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% - 50% - 0%).

	F9463009 - 96lm	White
	F9463057 - 96lm	Chrome
	F9463030 - 96lm	Black

## Wall System Minikelvin Flex Power Supply Integrated . Lamps



### Top LED

#### Lamp category:


LED

#### Socket:

Special base

#### Lamp type:

Top LED



### CERTIFICATIONS

