

WALL SYSTEM MINIKELVIN FLEX REMOTE POWER SUPPLY

Number of heads	1
Mounting	Wall surface
Lamps description	Top LED 4W 216 lm 3000K CRI 85
Luminaire luminous flux	See reference number
Voltage (V)	24
Environment	Indoor

OPTICAL

Aiming	Adjustable
Light distribution symmetry	Symmetric
Beam angle	111°

ELECTRICAL

Transformer availability	Separate item
Transformer mounting	Remote
Transformer type	Electronic dimmable
Emergency	Without
Insulation class	Class III

PHYSICAL

Construction material	Aluminium
Weight (kg)	0,28




Wall System Minikelvin Flex Remote Power Supply

designed by Antonio Citterio

Diffuse illumination lighting device for installation flush with the wall with remote driver. ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% - 50% - 0%).

● F9478009 - 96lm	White
● F9478057 - 96lm	Chrome
● F9478030 - 96lm	Black



CERTIFICATIONS



Wall System Minikelvin Flex Remote Power Supply . Accessories

Power Supply



60.8079

Constant Current Power Supply for LED. 24V/8W

Electronic transformer with constant voltage (24V) for LED. 220/240V, 50/60Hz.

Maximum lenght of 1.5 mm2 secondary conductor (m): 5



Wall System Minikelvin Flex Remote Power Supply

designed by Antonio Citterio

Diffuse illumination lighting device for installation flush with the wall with remote driver. ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% - 50% - 0%).

	F9478009 - 96lm	White
	F9478057 - 96lm	Chrome
	F9478030 - 96lm	Black

Wall System Minikelvin Flex Remote Power Supply . Lamps




Top LED

Lamp category:
LED

Socket:
Special base

Lamp type:
Top LED



CERTIFICATIONS

