

## WALL SYSTEM BACK I REMOTE POWER SUPPLY

<b>Number of heads</b>	I
<b>Mounting</b>	Wall surface
<b>Lamps description</b>	Top LED 6W 426 lm 3000K CRI 80
<b>Luminaire luminous flux</b>	See reference number
<b>Voltage (V)</b>	24
<b>Environment</b>	Indoor

### OPTICAL

<b>Aiming</b>	Adjustable
<b>Beam angle</b>	70°

### ELECTRICAL

<b>Transformer availability</b>	Separate item
<b>Transformer mounting</b>	Remote
<b>Transformer type</b>	Electronic
<b>Emergency</b>	Without
<b>Insulation class</b>	Class III

### PHYSICAL


<b>Construction material</b>	Aluminium
<b>Weight (kg)</b>	0,30




### Wall System Back I Remote Power Supply

designed by Antonio Citterio

Indirect-illumination lighting device for installation flush with the wall with remote driver.

 F9492057 - 268lm Chrome



### CERTIFICATIONS



## Wall System Back I Remote Power Supply . Accessories

### Power Supply



60.8079

#### Constant Current Power Supply for LED. 24V/8W

Electronic transformer with constant voltage (24V) for LED. 220/240V, 50/60Hz.

Maximum length of 1.5 mm<sup>2</sup> secondary conductor (m): 5

### Wall System Back I Remote Power Supply . Lamps



#### Top LED

#### Lamp category:

LED

#### Socket:

Special base

#### Lamp type:

Top LED




#### Wall System Back I Remote Power Supply

designed by Antonio Citterio

Indirect-illumination lighting device for installation flush with the wall with remote driver.

F9492057 - 268lm Chrome



#### CERTIFICATIONS

