

WALL SYSTEM BACK I REMOTE POWER SUPPLY OPTICAL SWITCH

Number of heads	I
Mounting	Wall surface
Lamps description	Top LED 6W 426 lm 3000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	24
Environment	Indoor

OPTICAL

Aiming	Adjustable
Beam angle	70°

ELECTRICAL

Transformer availability	Separate item
Transformer mounting	Remote
Transformer type	Electronic dimmable
Emergency	Without
Insulation class	Class III

PHYSICAL

Construction material	Aluminium
Weight (kg)	0,30




Wall System Back I Remote Power Supply Optical Switch

designed by Antonio Citterio

Indirect-illumination lighting device for installation flush with the wall with remote driver. ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% - 50% - 0%).

F9493057 - 268lm Chrome



CERTIFICATIONS



Wall System Back I Remote Power Supply Optical Switch . Accessories

Power Supply



60.8079

Constant Current Power Supply for LED. 24V/8W

Electronic transformer with constant voltage (24V) for LED. 220/240V, 50/60Hz.

Maximum length of 1.5 mm² secondary conductor (m): 5



Wall System Back I Remote Power Supply Optical Switch

designed by Antonio Citterio

Indirect-illumination lighting device for installation flush with the wall with remote driver. ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% - 50% - 0%).

F9493057 - 268lm Chrome

Wall System Back I Remote Power Supply Optical Switch . Lamps



Top LED

Lamp category:


LED

Socket:

Special base

Lamp type:

Top LED



CERTIFICATIONS

