

LIGHTLIGHT® WALL/SHOP-W|DISC 70

Number of heads	1
Mounting	LightLight® Wall
Lamps description	QR-70 BA15d 20/50W
Voltage (V)	12
Environment	Indoor

OPTICAL

Light controller description	Bare lamps
Aiming	Directional
Light distribution symmetry	Symmetric
Beam angle	24°, 8°

ELECTRICAL

Transformer availability	Separate item
Transformer mounting	Remote
Emergency	Without
Insulation class	Class III

PHYSICAL

Height (mm)	25
Spot diameter (mm)	74
Construction material	Aluminium
Weight (kg)	0,06



LightLight® Wall/Shop-W|Disc 70 designed by Hans Buschfeld

Picture luminaire to be installed on 12V wall track system. Track adapter integrated.

	BU35855A	Anodised aluminium
	BU35955B	Black
	BU35955P	Polished aluminium
	BU35855W	White



CERTIFICATIONS



LightLight® Wall/Shop-W|Disc 70 . Lamps



60.6369

QR-70

Lamp Watt:
20 W

Lamp category:
Halogen low voltage

Socket:
BA15d

Lamp angle:
24 °

Color temperature (K):
3000 °K

Catalog reference:
60.6369

Lamp type:
QR-70



60.6370

QR-70

Lamp Watt:
50 W

Lamp category:
Halogen low voltage

Socket:
BA15d

Lamp angle:
8 °

Color temperature (K):
3000 °K

Catalog reference:
60.6370

Lamp type:
QR-70



60.6371

QR-70

Lamp Watt:
50 W

Lamp category:
Halogen low voltage

Socket:
BA15d

Lamp angle:
24 °

Color temperature (K):
3000 °K

Catalog reference:
60.6371

Lamp type:
QR-70



LightLight® Wall/Shop-W|Disc 70 designed by Hans Buschfeld

Picture luminaire to be installed on
12V wall track system. Track adapter
integrated.

	BU35855A	Anodised aluminium
	BU35955B	Black
	BU35955P	Polished aluminium
	BU35855W	White



CERTIFICATIONS

