

## WALL PIERCING 2X LINE

<b>Lamps description</b>	LED White 2 x 6,4W 416 lm 2700K CRI>90
<b>Environment</b>	Indoor
<b>Notes</b>	LED modules included. For power supply and dimming interface see LED drivers (downloads).



### OPTICAL

<b>Aiming</b>	Fixed
<b>Light distribution symmetry</b>	Symmetric

### ELECTRICAL

<b>Control gear availability</b>	Included
<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Remote
<b>Transformer type</b>	Electronic
<b>Emergency</b>	Without
<b>Insulation class</b>	Class III


### Wall Piercing 2x Line designed by Ron Gilad

Soft technology semi-recessed luminaire for ceiling or wall mounting. Available in white LED or RGB versions. Control gear not included.


- SA.5023.5A120 White
- SA.5023.5A180 Aluminium

### PHYSICAL

<b>Weight (kg)</b>	5
--------------------	---



### CERTIFICATIONS



## Wall Piercing 2x Line . Lamps



### LED White 6.4W

#### Lamp Watt:

6.4 W

#### Lamp category:

LED

#### Color temperature (K):

2700 °K

#### Lamp type:

LED White


### Wall Piercing 2x Line

designed by Ron Gilad

Soft technology semi-recessed luminaire for ceiling or wall mounting. Available in white LED or RGB versions. Control gear not included.

○ SA.5023.5A120 White

● SA.5023.5A180 Aluminium



### CERTIFICATIONS

