

IN-FINITY 100 SUSPENSION DOWN 3000K GENERAL LIGHTING

Number of heads	1
Mounting	Pendant
Lamps description	Top LED 34,1W/m 3915 lm/m 3000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Suspension Down 3000K General Lighting

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	109°

ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic
Emergency	Without
Insulation class	Class I

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



- N10D053G30 565mm - 1578lm White
- N10D053G02 565mm - 1578lm Anodized Grey
- N10D053G14 565mm - 1578lm Black
- N10D083G30 845mm - 2367lm White
- N10D083G02 845mm - 2367lm Anodized Grey
- N10D083G14 845mm - 2367lm Black
- N10D113G30 1125mm - 3156lm White
- N10D113G02 1125mm - 3156lm Anodized Grey
- N10D113G14 1125mm - 3156lm Black
- N10D143G30 1405mm - 3945lm White
- N10D143G02 1405mm - 3945lm Anodized Grey
- N10D143G14 1405mm - 3945lm Black
- N10D163G30 1690mm - 4734lm White
- N10D163G02 1690mm - 4734lm Anodized Grey
- N10D163G14 1690mm - 4734lm Black
- N10D193G30 1970mm - 5523lm White
- N10D193G02 1970mm - 5523lm Anodized Grey
- N10D193G14 1970mm - 5523lm Black
- N10D253G30 2530mm - 7101lm White
- N10D253G02 2530mm - 7101lm Anodized Grey
- N10D253G14 2530mm - 7101lm Black
- N10D303G30 3095mm - 8679lm White
- N10D303G02 3095mm - 8679lm Anodized Grey
- N10D303G14 3095mm - 8679lm Black
- N10DFC3G30 Flat Corner - 3156lm White
- N10DFC3G02 Flat Corner - 3156lm Anodized Grey
- N10DFC3G14 Flat Corner - 3156lm Black
- N10DEM3G30 Emergency - 3945lm White
- N10DEM3G02 Emergency - 3945lm Anodized Grey
- N10DEM3G14 Emergency - 3945lm Black

In-Finity 100 Suspension Down 3000K General Lighting . Accessories

Structural



- 08.9054.40
- 08.9054.02
- 08.9054.NS
- 08.9054.06

Metal cover. Surface / Suspension Down. 100 mm

Metal cover for the different profiles. 2 unit kit.


Mounting



- 08.0030

Suspension kit

One unit Suspension kit (L = 4 m).
Maximum distance between the suspension cables: 2 m.



In-Finity 100 Suspension Down 3000K General Lighting

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- NI0D053G30 565mm - 1578lm White
- NI0D053G02 565mm - 1578lm Anodized Grey
- NI0D053G14 565mm - 1578lm Black
- NI0D083G30 845mm - 2367lm White
- NI0D083G02 845mm - 2367lm Anodized Grey
- NI0D083G14 845mm - 2367lm Black
- NI0D113G30 1125mm - 3156lm White
- NI0D113G02 1125mm - 3156lm Anodized Grey
- NI0D113G14 1125mm - 3156lm Black
- NI0D143G30 1405mm - 3945lm White
- NI0D143G02 1405mm - 3945lm Anodized Grey
- NI0D143G14 1405mm - 3945lm Black
- NI0D163G30 1690mm - 4734lm White
- NI0D163G02 1690mm - 4734lm Anodized Grey
- NI0D163G14 1690mm - 4734lm Black
- NI0D193G30 1970mm - 5523lm White
- NI0D193G02 1970mm - 5523lm Anodized Grey
- NI0D193G14 1970mm - 5523lm Black
- NI0D253G30 2530mm - 7101lm White
- NI0D253G02 2530mm - 7101lm Anodized Grey
- NI0D253G14 2530mm - 7101lm Black
- NI0D303G30 3095mm - 8679lm White
- NI0D303G02 3095mm - 8679lm Anodized Grey
- NI0D303G14 3095mm - 8679lm Black
- NI0DFC3G30 Flat Corner - 3156lm White
- NI0DFC3G02 Flat Corner - 3156lm Anodized Grey
- NI0DFC3G14 Flat Corner - 3156lm Black
- NI0DEM3G30 Emergency - 3945lm White
- NI0DEM3G02 Emergency - 3945lm Anodized Grey
- NI0DEM3G14 Emergency - 3945lm Black

In-Finity 100 Suspension Down 3000K General Lighting . Accessories

Electrical



08.0031.00

Power supply rose

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable

In-Finity 100 Suspension Down 3000K General Lighting . Lamps



Top LED

Lamp category:


LED

Socket:

Special base

Lamp type:

Top LED



In-Finity 100 Suspension Down 3000K General Lighting

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- NI0D053G30 565mm - 1578lm White
- NI0D053G02 565mm - 1578lm Anodized Grey
- NI0D053G14 565mm - 1578lm Black
- NI0D083G30 845mm - 2367lm White
- NI0D083G02 845mm - 2367lm Anodized Grey
- NI0D083G14 845mm - 2367lm Black
- NI0D113G30 1125mm - 3156lm White
- NI0D113G02 1125mm - 3156lm Anodized Grey
- NI0D113G14 1125mm - 3156lm Black
- NI0D143G30 1405mm - 3945lm White
- NI0D143G02 1405mm - 3945lm Anodized Grey
- NI0D143G14 1405mm - 3945lm Black
- NI0D163G30 1690mm - 4734lm White
- NI0D163G02 1690mm - 4734lm Anodized Grey
- NI0D163G14 1690mm - 4734lm Black
- NI0D193G30 1970mm - 5523lm White
- NI0D193G02 1970mm - 5523lm Anodized Grey
- NI0D193G14 1970mm - 5523lm Black
- NI0D253G30 2530mm - 7101lm White
- NI0D253G02 2530mm - 7101lm Anodized Grey
- NI0D253G14 2530mm - 7101lm Black
- NI0D303G30 3095mm - 8679lm White
- NI0D303G02 3095mm - 8679lm Anodized Grey
- NI0D303G14 3095mm - 8679lm Black
- NI0DFC3G30 Flat Corner - 3156lm White
- NI0DFC3G02 Flat Corner - 3156lm Anodized Grey
- NI0DFC3G14 Flat Corner - 3156lm Black
- NI0DEM3G30 Emergency - 3945lm White
- NI0DEM3G02 Emergency - 3945lm Anodized Grey
- NI0DEM3G14 Emergency - 3945lm Black