


## IN-FINITY 100 SUSPENSION DOWN 3000K MICRO-PRISMATIC DIFFUSER

<b>Number of heads</b>	1
<b>Mounting</b>	Pendant
<b>Lamps description</b>	Top LED 34,1W/m 3915 lm/m 3000K CRI 80
<b>Luminaire luminous flux</b>	See reference number
<b>Voltage (V)</b>	220/240
<b>Environment</b>	Indoor
<b>Notes</b>	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19° light beam. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



**In-Finity 100 Suspension Down 3000K Micro-Prismatic Diffuser**  
designed by FLOS Architectural

### OPTICAL

<b>Aiming</b>	Fixed
<b>Light distribution symmetry</b>	Symmetric
<b>Beam angle</b>	77°

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

### ELECTRICAL

<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Integral
<b>Transformer type</b>	Electronic
<b>Emergency</b>	Without
<b>Insulation class</b>	Class I

- N10D053U30 565mm - 1607lm White
- N10D053U02 565mm - 1607lm Anodized Grey
- N10D053U14 565mm - 1607lm Black
- N10D083U30 845mm - 2410lm White
- N10D083U02 845mm - 2410lm Anodized Grey
- N10D083U14 845mm - 2410lm Black
- N10D113U30 1125mm - 3214lm White
- N10D113U02 1125mm - 3214lm Anodized Grey
- N10D113U14 1125mm - 3214lm Black
- N10D143U30 1405mm - 4017lm White
- N10D143U02 1405mm - 4017lm Anodized Grey
- N10D143U14 1405mm - 4017lm Black
- N10D163U30 1690mm - 4821lm White
- N10D163U02 1690mm - 4821lm Anodized Grey
- N10D163U14 1690mm - 4821lm Black
- N10D193U30 1970mm - 5624lm White
- N10D193U02 1970mm - 5624lm Anodized Grey
- N10D193U14 1970mm - 5624lm Black
- N10D253U30 2530mm - 7231lm White
- N10D253U02 2530mm - 7231lm Anodized Grey
- N10D253U14 2530mm - 7231lm Black
- N10D303U30 3095mm - 8838lm White
- N10D303U02 3095mm - 8838lm Anodized Grey
- N10D303U14 3095mm - 8838lm Black
- N10DFC3U30 Flat Corner - 3214lm White
- N10DFC3U02 Flat Corner - 3214lm Anodized Grey
- N10DFC3U14 Flat Corner - 3214lm Black
- N10DEM3U30 Emergency - 4017lm White
- N10DEM3U02 Emergency - 4017lm Anodized Grey
- N10DEM3U14 Emergency - 4017lm Black

### PHYSICAL

<b>Construction material</b>	Aluminium
------------------------------	-----------



## In-Finity 100 Suspension Down 3000K Micro-Prismatic Diffuser . Accessories

### Structural



- 08.9054.40
- 08.9054.02
- 08.9054.NS
- 08.9054.06

#### Metal cover. Surface / Suspension Down. 100 mm

Metal cover for the different profiles. 2 unit kit.


### Mounting



- 08.0030

#### Suspension kit

One unit Suspension kit (L = 4 m).  
Maximum distance between the suspension cables: 2 m.



### In-Finity 100 Suspension Down 3000K Micro-Prismatic Diffuser designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- NI0D053U30 565mm - 1607lm White
- NI0D053U02 565mm - 1607lm Anodized Grey
- NI0D053U14 565mm - 1607lm Black
- NI0D083U30 845mm - 2410lm White
- NI0D083U02 845mm - 2410lm Anodized Grey
- NI0D083U14 845mm - 2410lm Black
- NI0D113U30 1125mm - 3214lm White
- NI0D113U02 1125mm - 3214lm Anodized Grey
- NI0D113U14 1125mm - 3214lm Black
- NI0D143U30 1405mm - 4017lm White
- NI0D143U02 1405mm - 4017lm Anodized Grey
- NI0D143U14 1405mm - 4017lm Black
- NI0D163U30 1690mm - 4821lm White
- NI0D163U02 1690mm - 4821lm Anodized Grey
- NI0D163U14 1690mm - 4821lm Black
- NI0D193U30 1970mm - 5624lm White
- NI0D193U02 1970mm - 5624lm Anodized Grey
- NI0D193U14 1970mm - 5624lm Black
- NI0D253U30 2530mm - 7231lm White
- NI0D253U02 2530mm - 7231lm Anodized Grey
- NI0D253U14 2530mm - 7231lm Black
- NI0D303U30 3095mm - 8838lm White
- NI0D303U02 3095mm - 8838lm Anodized Grey
- NI0D303U14 3095mm - 8838lm Black
- NI0DFC3U30 Flat Corner - 3214lm White
- NI0DFC3U02 Flat Corner - 3214lm Anodized Grey
- NI0DFC3U14 Flat Corner - 3214lm Black
- NI0DEM3U30 Emergency - 4017lm White
- NI0DEM3U02 Emergency - 4017lm Anodized Grey
- NI0DEM3U14 Emergency - 4017lm Black

## In-Finity 100 Suspension Down 3000K Micro-Prismatic Diffuser . Accessories

### Electrical



08.0031.00

#### Power supply rose

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable

## In-Finity 100 Suspension Down 3000K Micro-Prismatic Diffuser . Lamps



#### Top LED

#### Lamp category:


LED

#### Socket:

Special base

#### Lamp type:

Top LED



### In-Finity 100 Suspension Down 3000K Micro-Prismatic Diffuser designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- NI0D053U30 565mm - 1607lm White
- NI0D053U02 565mm - 1607lm Anodized Grey
- NI0D053U14 565mm - 1607lm Black
- NI0D083U30 845mm - 2410lm White
- NI0D083U02 845mm - 2410lm Anodized Grey
- NI0D083U14 845mm - 2410lm Black
- NI0D113U30 1125mm - 3214lm White
- NI0D113U02 1125mm - 3214lm Anodized Grey
- NI0D113U14 1125mm - 3214lm Black
- NI0D143U30 1405mm - 4017lm White
- NI0D143U02 1405mm - 4017lm Anodized Grey
- NI0D143U14 1405mm - 4017lm Black
- NI0D163U30 1690mm - 4821lm White
- NI0D163U02 1690mm - 4821lm Anodized Grey
- NI0D163U14 1690mm - 4821lm Black
- NI0D193U30 1970mm - 5624lm White
- NI0D193U02 1970mm - 5624lm Anodized Grey
- NI0D193U14 1970mm - 5624lm Black
- NI0D253U30 2530mm - 7231lm White
- NI0D253U02 2530mm - 7231lm Anodized Grey
- NI0D253U14 2530mm - 7231lm Black
- NI0D303U30 3095mm - 8838lm White
- NI0D303U02 3095mm - 8838lm Anodized Grey
- NI0D303U14 3095mm - 8838lm Black
- NI0DFC3U30 Flat Corner - 3214lm White
- NI0DFC3U02 Flat Corner - 3214lm Anodized Grey
- NI0DFC3U14 Flat Corner - 3214lm Black
- NI0DEM3U30 Emergency - 4017lm White
- NI0DEM3U02 Emergency - 4017lm Anodized Grey
- NI0DEM3U14 Emergency - 4017lm Black