


## IN-FINITY 100 SUSPENSION DOWN 4000K GENERAL LIGHTING

<b>Number of heads</b>	1
<b>Mounting</b>	Pendant
<b>Lamps description</b>	Top LED 34,1W/m 4228 lm/m 4000K CRI 80
<b>Luminaire luminous flux</b>	See reference number
<b>Voltage (V)</b>	220/240
<b>Environment</b>	Indoor
<b>Notes</b>	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



### In-Finity 100 Suspension Down 4000K General Lighting

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

### OPTICAL

<b>Aiming</b>	Fixed
<b>Light distribution symmetry</b>	Symmetric
<b>Beam angle</b>	109°

### ELECTRICAL

<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Integral
<b>Transformer type</b>	Electronic
<b>Emergency</b>	Without
<b>Insulation class</b>	Class I

### PHYSICAL

<b>Construction material</b>	Aluminium
------------------------------	-----------



- N10D054G30 565mm - 1555lm White
- N10D054G02 565mm - 1555lm Anodized Grey
- N10D054G14 565mm - 1555lm Black
- N10D084G30 845mm - 2333lm White
- N10D084G02 845mm - 2333lm Anodized Grey
- N10D084G14 845mm - 2333lm Black
- N10D114G30 1125mm - 3111lm White
- N10D114G02 1125mm - 3111lm Anodized Grey
- N10D114G14 1125mm - 3111lm Black
- N10D144G30 1405mm - 3889lm White
- N10D144G02 1405mm - 3889lm Anodized Grey
- N10D144G14 1405mm - 3889lm Black
- N10D164G30 1690mm - 4667lm White
- N10D164G02 1690mm - 4667lm Anodized Grey
- N10D164G14 1690mm - 4667lm Black
- N10D194G30 1970mm - 5445lm White
- N10D194G02 1970mm - 5445lm Anodized Grey
- N10D194G14 1970mm - 5445lm Black
- N10D254G30 2530mm - 7001lm White
- N10D254G02 2530mm - 7001lm Anodized Grey
- N10D254G14 2530mm - 7001lm Black
- N10D304G30 3095mm - 8557lm White
- N10D304G02 3095mm - 8557lm Anodized Grey
- N10D304G14 3095mm - 8557lm Black
- N10DFC4G30 Flat Corner - 3111lm White
- N10DFC4G02 Flat Corner - 3111lm Anodized Grey
- N10DFC4G14 Flat Corner - 3111lm Black
- N10DEM4G30 Emergency - 3889lm White
- N10DEM4G02 Emergency - 3889lm Anodized Grey
- N10DEM4G14 Emergency - 3889lm Black

## In-Finity 100 Suspension Down 4000K General Lighting . Accessories

### Structural



- 08.9054.40
- 08.9054.02
- 08.9054.NS
- 08.9054.06

#### Metal cover. Surface / Suspension Down. 100 mm

Metal cover for the different profiles. 2 unit kit.


### Mounting



- 08.0030

#### Suspension kit

One unit Suspension kit (L = 4 m).  
Maximum distance between the suspension cables: 2 m.



### In-Finity 100 Suspension Down 4000K General Lighting

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- NI0D054G30 565mm - 1555lm White
- NI0D054G02 565mm - 1555lm Anodized Grey
- NI0D054G14 565mm - 1555lm Black
- NI0D084G30 845mm - 2333lm White
- NI0D084G02 845mm - 2333lm Anodized Grey
- NI0D084G14 845mm - 2333lm Black
- NI0D114G30 1125mm - 3111lm White
- NI0D114G02 1125mm - 3111lm Anodized Grey
- NI0D114G14 1125mm - 3111lm Black
- NI0D144G30 1405mm - 3889lm White
- NI0D144G02 1405mm - 3889lm Anodized Grey
- NI0D144G14 1405mm - 3889lm Black
- NI0D164G30 1690mm - 4667lm White
- NI0D164G02 1690mm - 4667lm Anodized Grey
- NI0D164G14 1690mm - 4667lm Black
- NI0D194G30 1970mm - 5445lm White
- NI0D194G02 1970mm - 5445lm Anodized Grey
- NI0D194G14 1970mm - 5445lm Black
- NI0D254G30 2530mm - 7001lm White
- NI0D254G02 2530mm - 7001lm Anodized Grey
- NI0D254G14 2530mm - 7001lm Black
- NI0D304G30 3095mm - 8557lm White
- NI0D304G02 3095mm - 8557lm Anodized Grey
- NI0D304G14 3095mm - 8557lm Black
- NI0DFC4G30 Flat Corner - 3111lm White
- NI0DFC4G02 Flat Corner - 3111lm Anodized Grey
- NI0DFC4G14 Flat Corner - 3111lm Black
- NI0DEM4G30 Emergency - 3889lm White
- NI0DEM4G02 Emergency - 3889lm Anodized Grey
- NI0DEM4G14 Emergency - 3889lm Black

## In-Finity 100 Suspension Down 4000K General Lighting . Accessories

### Electrical



08.0031.00

#### Power supply rose

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable

## In-Finity 100 Suspension Down 4000K General Lighting . Lamps



#### Top LED

#### Lamp category:


LED

#### Socket:

Special base

#### Lamp type:

Top LED



## In-Finity 100 Suspension Down 4000K General Lighting

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- NI0D054G30 565mm - 1555lm White
- NI0D054G02 565mm - 1555lm Anodized Grey
- NI0D054G14 565mm - 1555lm Black
- NI0D084G30 845mm - 2333lm White
- NI0D084G02 845mm - 2333lm Anodized Grey
- NI0D084G14 845mm - 2333lm Black
- NI0D114G30 1125mm - 3111lm White
- NI0D114G02 1125mm - 3111lm Anodized Grey
- NI0D114G14 1125mm - 3111lm Black
- NI0D144G30 1405mm - 3889lm White
- NI0D144G02 1405mm - 3889lm Anodized Grey
- NI0D144G14 1405mm - 3889lm Black
- NI0D164G30 1690mm - 4667lm White
- NI0D164G02 1690mm - 4667lm Anodized Grey
- NI0D164G14 1690mm - 4667lm Black
- NI0D194G30 1970mm - 5445lm White
- NI0D194G02 1970mm - 5445lm Anodized Grey
- NI0D194G14 1970mm - 5445lm Black
- NI0D254G30 2530mm - 7001lm White
- NI0D254G02 2530mm - 7001lm Anodized Grey
- NI0D254G14 2530mm - 7001lm Black
- NI0D304G30 3095mm - 8557lm White
- NI0D304G02 3095mm - 8557lm Anodized Grey
- NI0D304G14 3095mm - 8557lm Black
- NI0DFC4G30 Flat Corner - 3111lm White
- NI0DFC4G02 Flat Corner - 3111lm Anodized Grey
- NI0DFC4G14 Flat Corner - 3111lm Black
- NI0DEM4G30 Emergency - 3889lm White
- NI0DEM4G02 Emergency - 3889lm Anodized Grey
- NI0DEM4G14 Emergency - 3889lm Black