


IN-FINITY 100 SUSPENSION DOWN 4000K MICRO-PRISMATIC DIFFUSER

Number of heads	1
Mounting	Pendant
Lamps description	Top LED 34,1W/m 4228 lm/m 4000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Suspension Down 4000K Micro-Prismatic Diffuser
designed by FLOS Architectural

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	77°

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic
Emergency	Without
Insulation class	Class I

- N10D054U30 565mm - 1580lm White
- N10D054U02 565mm - 1580lm Anodized Grey
- N10D054U14 565mm - 1580lm Black
- N10D084U30 845mm - 2371lm White
- N10D084U02 845mm - 2371lm Anodized Grey
- N10D084U14 845mm - 2371lm Black
- N10D114U30 1125mm - 3161lm White
- N10D114U02 1125mm - 3161lm Anodized Grey
- N10D114U14 1125mm - 3161lm Black
- N10D144U30 1405mm - 3952lm White
- N10D144U02 1405mm - 3952lm Anodized Grey
- N10D144U14 1405mm - 3952lm Black
- N10D164U30 1690mm - 4742lm White
- N10D164U02 1690mm - 4742lm Anodized Grey
- N10D164U14 1690mm - 4742lm Black
- N10D194U30 1970mm - 5533lm White
- N10D194U02 1970mm - 5533lm Anodized Grey
- N10D194U14 1970mm - 5533lm Black
- N10D254U30 2530mm - 7114lm White
- N10D254U02 2530mm - 7114lm Anodized Grey
- N10D254U14 2530mm - 7114lm Black
- N10D304U30 3095mm - 8695lm White
- N10D304U02 3095mm - 8695lm Anodized Grey
- N10D304U14 3095mm - 8695lm Black
- N10DFC4U30 Flat Corner - 3161lm White
- N10DFC4U02 Flat Corner - 3161lm Anodized Grey
- N10DFC4U14 Flat Corner - 3161lm Black
- N10DEM4U30 Emergency - 3952lm White
- N10DEM4U02 Emergency - 3952lm Anodized Grey
- N10DEM4U14 Emergency - 3952lm Black

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



In-Finity 100 Suspension Down 4000K Micro-Prismatic Diffuser . Accessories

Structural



- 08.9054.40
- 08.9054.02
- 08.9054.NS
- 08.9054.06

Metal cover. Surface / Suspension Down. 100 mm

Metal cover for the different profiles. 2 unit kit.


Mounting



- 08.0030

Suspension kit

One unit Suspension kit (L = 4 m).
Maximum distance between the suspension cables: 2 m.



In-Finity 100 Suspension Down 4000K Micro-Prismatic Diffuser designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- NI0D054U30 565mm - 1580lm White
- NI0D054U02 565mm - 1580lm Anodized Grey
- NI0D054U14 565mm - 1580lm Black
- NI0D084U30 845mm - 2371lm White
- NI0D084U02 845mm - 2371lm Anodized Grey
- NI0D084U14 845mm - 2371lm Black
- NI0D114U30 1125mm - 3161lm White
- NI0D114U02 1125mm - 3161lm Anodized Grey
- NI0D114U14 1125mm - 3161lm Black
- NI0D144U30 1405mm - 3952lm White
- NI0D144U02 1405mm - 3952lm Anodized Grey
- NI0D144U14 1405mm - 3952lm Black
- NI0D164U30 1690mm - 4742lm White
- NI0D164U02 1690mm - 4742lm Anodized Grey
- NI0D164U14 1690mm - 4742lm Black
- NI0D194U30 1970mm - 5533lm White
- NI0D194U02 1970mm - 5533lm Anodized Grey
- NI0D194U14 1970mm - 5533lm Black
- NI0D254U30 2530mm - 7114lm White
- NI0D254U02 2530mm - 7114lm Anodized Grey
- NI0D254U14 2530mm - 7114lm Black
- NI0D304U30 3095mm - 8695lm White
- NI0D304U02 3095mm - 8695lm Anodized Grey
- NI0D304U14 3095mm - 8695lm Black
- NI0DFC4U30 Flat Corner - 3161lm White
- NI0DFC4U02 Flat Corner - 3161lm Anodized Grey
- NI0DFC4U14 Flat Corner - 3161lm Black
- NI0DEM4U30 Emergency - 3952lm White
- NI0DEM4U02 Emergency - 3952lm Anodized Grey
- NI0DEM4U14 Emergency - 3952lm Black

In-Finity 100 Suspension Down 4000K Micro-Prismatic Diffuser . Accessories

Electrical



08.0031.00

Power supply rose

Power supply rose for the hanging installation of the In-Finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable

In-Finity 100 Suspension Down 4000K Micro-Prismatic Diffuser . Lamps



Top LED

Lamp category:


LED

Socket:

Special base

Lamp type:

Top LED



In-Finity 100 Suspension Down 4000K Micro-Prismatic Diffuser designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- N10D054U30 565mm - 1580lm White
- N10D054U02 565mm - 1580lm Anodized Grey
- N10D054U14 565mm - 1580lm Black
- N10D084U30 845mm - 2371lm White
- N10D084U02 845mm - 2371lm Anodized Grey
- N10D084U14 845mm - 2371lm Black
- N10D114U30 1125mm - 3161lm White
- N10D114U02 1125mm - 3161lm Anodized Grey
- N10D114U14 1125mm - 3161lm Black
- N10D144U30 1405mm - 3952lm White
- N10D144U02 1405mm - 3952lm Anodized Grey
- N10D144U14 1405mm - 3952lm Black
- N10D164U30 1690mm - 4742lm White
- N10D164U02 1690mm - 4742lm Anodized Grey
- N10D164U14 1690mm - 4742lm Black
- N10D194U30 1970mm - 5533lm White
- N10D194U02 1970mm - 5533lm Anodized Grey
- N10D194U14 1970mm - 5533lm Black
- N10D254U30 2530mm - 7114lm White
- N10D254U02 2530mm - 7114lm Anodized Grey
- N10D254U14 2530mm - 7114lm Black
- N10D304U30 3095mm - 8695lm White
- N10D304U02 3095mm - 8695lm Anodized Grey
- N10D304U14 3095mm - 8695lm Black
- N10DFC4U30 Flat Corner - 3161lm White
- N10DFC4U02 Flat Corner - 3161lm Anodized Grey
- N10DFC4U14 Flat Corner - 3161lm Black
- N10DEM4U30 Emergency - 3952lm White
- N10DEM4U02 Emergency - 3952lm Anodized Grey
- N10DEM4U14 Emergency - 3952lm Black