


IN-FINITY 100 SUSPENSION UP & DOWN 3000K GENERAL LIGHTING

Number of heads	1
Mounting	Pendant up & down
Lamps description	Top LED 46,9W/m 3000K CRI 80 1536 lm/m UP - 3915 lm/m DOWN
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Suspension Up & Down 3000K General Lighting
designed by FLOS Architectural

OPTICAL

Aiming	Fixed
Light distribution symmetry	Direct - Indirect
Beam angle	109°

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.


ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic
Emergency	Without
Insulation class	Class I

- N10U113G30 1125mm - 4220lm White
- N10U113G02 1125mm - 4220lm Anodized Grey
- N10U113G14 1125mm - 4220lm Black
- N10U143G30 1405mm - 5275lm White
- N10U143G02 1405mm - 5275lm Anodized Grey
- N10U143G14 1405mm - 5275lm Black
- N10U193G30 1970mm - 7386lm White
- N10U193G02 1970mm - 7386lm Anodized Grey
- N10U193G14 1970mm - 7386lm Black
- N10U303G30 3095mm - 11606lm White
- N10U303G02 3095mm - 11606lm Anodized Grey
- N10U303G14 3095mm - 11606lm Black
- N10UFC3G30 Flat Corner - 4220lm White
- N10UFC3G02 Flat Corner - 4220lm Anodized Grey
- N10UFC3G14 Flat Corner - 4220lm Black
- N10UEM3G30 Emergency - 5275lm White
- N10UEM3G02 Emergency - 5275lm Anodized Grey
- N10UEM3G14 Emergency - 5275lm Black
- N10U083G30 845mm - 3165lm White
- N10U083G02 845mm - 3165lm Anodized Grey
- N10U083G14 845mm - 3165lm Black
- N10U163G30 1690mm - 6330lm White
- N10U163G02 1690mm - 6330lm Anodized Grey
- N10U163G14 1690mm - 6330lm Black
- N10U253G30 2530mm - 9496lm White
- N10U253G02 2530mm - 9496lm Anodized Grey
- N10U253G14 2530mm - 9496lm Black

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



In-Finity 100 Suspension Up & Down 3000K General Lighting . Accessories

Structural



- 08.9058.40
- 08.9058.02
- 08.9058.NS
- 08.9058.06

Metal cover. Suspension Up & Down. 100 mm

Metal cover for the different profiles. 2 unit kit.


Mounting



- 08.0030

Suspension kit


One unit Suspension kit (L = 4 m).
Maximum distance between the suspension cables: 2 m.



In-Finity 100 Suspension Up & Down 3000K General Lighting designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N10U113G30 1125mm - 4220lm White
- N10U113G02 1125mm - 4220lm Anodized Grey
- N10U113G14 1125mm - 4220lm Black
- N10U143G30 1405mm - 5275lm White
- N10U143G02 1405mm - 5275lm Anodized Grey
- N10U143G14 1405mm - 5275lm Black
- N10U193G30 1970mm - 7386lm White
- N10U193G02 1970mm - 7386lm Anodized Grey
- N10U193G14 1970mm - 7386lm Black
- N10U303G30 3095mm - 11606lm White
- N10U303G02 3095mm - 11606lm Anodized Grey
- N10U303G14 3095mm - 11606lm Black
- N10UFC3G30 Flat Corner - 4220lm White
- N10UFC3G02 Flat Corner - 4220lm Anodized Grey
- N10UFC3G14 Flat Corner - 4220lm Black
- N10UEM3G30 Emergency - 5275lm White
- N10UEM3G02 Emergency - 5275lm Anodized Grey
- N10UEM3G14 Emergency - 5275lm Black
- N10U083G30 845mm - 3165lm White
- N10U083G02 845mm - 3165lm Anodized Grey
- N10U083G14 845mm - 3165lm Black
- N10U163G30 1690mm - 6330lm White
- N10U163G02 1690mm - 6330lm Anodized Grey
- N10U163G14 1690mm - 6330lm Black
- N10U253G30 2530mm - 9496lm White
- N10U253G02 2530mm - 9496lm Anodized Grey
- N10U253G14 2530mm - 9496lm Black



In-Finity 100 Suspension Up & Down 3000K General Lighting . Accessories

Electrical



08.0031.00

Power supply rose

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable

In-Finity 100 Suspension Up & Down 3000K General Lighting . Lamps



Top LED

Lamp category:


LED

Socket:

Special base

Lamp type:

Top LED



In-Finity 100 Suspension Up & Down 3000K General Lighting designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N10U113G30 1125mm - 4220lm White
- N10U113G02 1125mm - 4220lm Anodized Grey
- N10U113G14 1125mm - 4220lm Black
- N10U143G30 1405mm - 5275lm White
- N10U143G02 1405mm - 5275lm Anodized Grey
- N10U143G14 1405mm - 5275lm Black
- N10U193G30 1970mm - 7386lm White
- N10U193G02 1970mm - 7386lm Anodized Grey
- N10U193G14 1970mm - 7386lm Black
- N10U303G30 3095mm - 11606lm White
- N10U303G02 3095mm - 11606lm Anodized Grey
- N10U303G14 3095mm - 11606lm Black
- N10UFC3G30 Flat Corner - 4220lm White
- N10UFC3G02 Flat Corner - 4220lm Anodized Grey
- N10UFC3G14 Flat Corner - 4220lm Black
- N10UEM3G30 Emergency - 5275lm White
- N10UEM3G02 Emergency - 5275lm Anodized Grey
- N10UEM3G14 Emergency - 5275lm Black
- N10U083G30 845mm - 3165lm White
- N10U083G02 845mm - 3165lm Anodized Grey
- N10U083G14 845mm - 3165lm Black
- N10U163G30 1690mm - 6330lm White
- N10U163G02 1690mm - 6330lm Anodized Grey
- N10U163G14 1690mm - 6330lm Black
- N10U253G30 2530mm - 9496lm White
- N10U253G02 2530mm - 9496lm Anodized Grey
- N10U253G14 2530mm - 9496lm Black

