


IN-FINITY 100 SUSPENSION UP & DOWN 3000K MICRO-PRISMATIC DIFFUSER

Number of heads	1
Mounting	Pendant up & down
Lamps description	Top LED 46,9W/m 3000K CRI 80 1536 lm/m UP - 3915 lm/m DOWN
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Suspension Up & Down 3000K Micro-Prismatic Diffuser

designed by FLOS Architectural

OPTICAL

Aiming	Fixed
Light distribution symmetry	Direct - Indirect
Beam angle	77°

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.


ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic
Emergency	Without
Insulation class	Class I

- N10U113U30 1125mm - 4278lm White
- N10U113U02 1125mm - 4278lm Anodized Grey
- N10U113U14 1125mm - 4278lm Black
- N10U143U30 1405mm - 5348lm White
- N10U143U02 1405mm - 5348lm Anodized Grey
- N10U143U14 1405mm - 5348lm Black
- N10U193U30 1970mm - 7487lm White
- N10U193U02 1970mm - 7487lm Anodized Grey
- N10U193U14 1970mm - 7487lm Black
- N10U303U30 3095mm - 11765lm White
- N10U303U02 3095mm - 11765lm Anodized Grey
- N10U303U14 3095mm - 11765lm Black
- N10UFC3U30 Flat Corner - 4278lm White
- N10UFC3U02 Flat Corner - 4278lm Anodized Grey
- N10UFC3U14 Flat Corner - 4278lm Black
- N10UEM3U30 Emergency - 5348lm White
- N10UEM3U02 Emergency - 5348lm Anodized Grey
- N10UEM3U14 Emergency - 5348lm Black
- N10U083U30 845mm - 3208lm White
- N10U083U02 845mm - 3208lm Anodized Grey
- N10U083U14 845mm - 3208lm Black
- N10U163U30 1690mm - 6417lm White
- N10U163U02 1690mm - 6417lm Anodized Grey
- N10U163U14 1690mm - 6417lm Black
- N10U253U30 2530mm - 9626lm White
- N10U253U02 2530mm - 9626lm Anodized Grey
- N10U253U14 2530mm - 9626lm Black

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



In-Finity 100 Suspension Up & Down 3000K Micro-Prismatic Diffuser . Accessories


Structural



- 08.9058.40
- 08.9058.02
- 08.9058.NS
- 08.9058.06

Metal cover. Suspension Up & Down. 100 mm

Metal cover for the different profiles. 2 unit kit.



In-Finity 100 Suspension Up & Down 3000K Micro-Prismatic Diffuser

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N10U113U30 1125mm - 4278lm White
- N10U113U02 1125mm - 4278lm Anodized Grey
- N10U113U14 1125mm - 4278lm Black
- N10U143U30 1405mm - 5348lm White
- N10U143U02 1405mm - 5348lm Anodized Grey
- N10U143U14 1405mm - 5348lm Black
- N10U193U30 1970mm - 7487lm White
- N10U193U02 1970mm - 7487lm Anodized Grey
- N10U193U14 1970mm - 7487lm Black
- N10U303U30 3095mm - 11765lm White
- N10U303U02 3095mm - 11765lm Anodized Grey
- N10U303U14 3095mm - 11765lm Black
- N10UFC3U30 Flat Corner - 4278lm White
- N10UFC3U02 Flat Corner - 4278lm Anodized Grey
- N10UFC3U14 Flat Corner - 4278lm Black
- N10UEM3U30 Emergency - 5348lm White
- N10UEM3U02 Emergency - 5348lm Anodized Grey
- N10UEM3U14 Emergency - 5348lm Black
- N10U083U30 845mm - 3208lm White
- N10U083U02 845mm - 3208lm Anodized Grey
- N10U083U14 845mm - 3208lm Black
- N10U163U30 1690mm - 6417lm White
- N10U163U02 1690mm - 6417lm Anodized Grey
- N10U163U14 1690mm - 6417lm Black
- N10U253U30 2530mm - 9626lm White
- N10U253U02 2530mm - 9626lm Anodized Grey
- N10U253U14 2530mm - 9626lm Black

Mounting



- 08.0030

Suspension kit

One unit Suspension kit (L = 4 m).
Maximum distance between the suspension cables: 2 m.



In-Finity 100 Suspension Up & Down 3000K Micro-Prismatic Diffuser . Accessories

Electrical



08.0031.00

Power supply rose

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable

In-Finity 100 Suspension Up & Down 3000K Micro-Prismatic Diffuser . Lamps



Top LED

Lamp category:


LED

Socket:

Special base

Lamp type:

Top LED



In-Finity 100 Suspension Up & Down 3000K Micro-Prismatic Diffuser

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N10U113U30 1125mm - 4278lm White
- N10U113U02 1125mm - 4278lm Anodized Grey
- N10U113U14 1125mm - 4278lm Black
- N10U143U30 1405mm - 5348lm White
- N10U143U02 1405mm - 5348lm Anodized Grey
- N10U143U14 1405mm - 5348lm Black
- N10U193U30 1970mm - 7487lm White
- N10U193U02 1970mm - 7487lm Anodized Grey
- N10U193U14 1970mm - 7487lm Black
- N10U303U30 3095mm - 11765lm White
- N10U303U02 3095mm - 11765lm Anodized Grey
- N10U303U14 3095mm - 11765lm Black
- N10UFC3U30 Flat Corner - 4278lm White
- N10UFC3U02 Flat Corner - 4278lm Anodized Grey
- N10UFC3U14 Flat Corner - 4278lm Black
- N10UEM3U30 Emergency - 5348lm White
- N10UEM3U02 Emergency - 5348lm Anodized Grey
- N10UEM3U14 Emergency - 5348lm Black
- N10U083U30 845mm - 3208lm White
- N10U083U02 845mm - 3208lm Anodized Grey
- N10U083U14 845mm - 3208lm Black
- N10U163U30 1690mm - 6417lm White
- N10U163U02 1690mm - 6417lm Anodized Grey
- N10U163U14 1690mm - 6417lm Black
- N10U253U30 2530mm - 9626lm White
- N10U253U02 2530mm - 9626lm Anodized Grey
- N10U253U14 2530mm - 9626lm Black

