


IN-FINITY 100 SUSPENSION UP & DOWN 3000K MICRO-PRISMATIC DIFFUSER DALI

Number of heads	1
Mounting	Pendant up & down
Lamps description	Top LED 46,9W/m 3000K CRI 80 1536 lm/m UP - 3915 lm/m DOWN
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

OPTICAL

Aiming	Fixed
Light distribution symmetry	Direct - Indirect
Beam angle	77°

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.


ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic dimmable dali
Emergency	Without
Insulation class	Class I

- N10U113U30.DA 1125mm - 4278lm **White**
- N10U113U02.DA 1125mm - 4278lm **Anodized Grey**
- N10U113U14.DA 1125mm - 4278lm **Black**
- N10U143U30.DA 1405mm - 5348lm **White**
- N10U143U02.DA 1405mm - 5348lm **Anodized Grey**
- N10U143U14.DA 1405mm - 5348lm **Black**
- N10U193U30.DA 1970mm - 7487lm **White**
- N10U193U02.DA 1970mm - 7487lm **Anodized Grey**
- N10U193U14.DA 1970mm - 7487lm **Black**
- N10U303U30.DA 3095mm - 11765lm **White**
- N10U303U02.DA 3095mm - 11765lm **Anodized Grey**
- N10U303U14.DA 3095mm - 11765lm **Black**
- N10UFC3U30.DA Flat Corner - 4278lm **White**
- N10UFC3U02.DA Flat Corner - 4278lm **Anodized Grey**
- N10UFC3U14.DA Flat Corner - 4278lm **Black**
- N10UEM3U30.DA Emergency - 5348lm **White**
- N10UEM3U02.DA Emergency - 5348lm **Anodized Grey**
- N10UEM3U14.DA Emergency - 5348lm **Black**
- N10U083U30.DA 845mm - 3208lm **White**
- N10U083U02.DA 845mm - 3208lm **Anodized Grey**
- N10U083U14.DA 845mm - 3208lm **Black**
- N10U163U30.DA 1690mm - 6417lm **White**
- N10U163U02.DA 1690mm - 6417lm **Anodized Grey**
- N10U163U14.DA 1690mm - 6417lm **Black**
- N10U253U30.DA 2530mm - 9626lm **White**
- N10U253U02.DA 2530mm - 9626lm **Anodized Grey**
- N10U253U14.DA 2530mm - 9626lm **Black**

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



In-Finity 100 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali . Accessories

Structural



- 08.9058.40
- 08.9058.02
- 08.9058.NS
- 08.9058.06

Metal cover. Suspension Up & Down. 100 mm

Metal cover for the different profiles. 2 unit kit.


Mounting



- 08.0030

Suspension kit

One unit Suspension kit (L = 4 m).
Maximum distance between the suspension cables: 2 m.



In-Finity 100 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N10U113U30.DA 1125mm - 4278lm **White**
- N10U113U02.DA 1125mm - 4278lm **Anodized Grey**
- N10U113U14.DA 1125mm - 4278lm **Black**
- N10U143U30.DA 1405mm - 5348lm **White**
- N10U143U02.DA 1405mm - 5348lm **Anodized Grey**
- N10U143U14.DA 1405mm - 5348lm **Black**
- N10U193U30.DA 1970mm - 7487lm **White**
- N10U193U02.DA 1970mm - 7487lm **Anodized Grey**
- N10U193U14.DA 1970mm - 7487lm **Black**
- N10U303U30.DA 3095mm - 11765lm **White**
- N10U303U02.DA 3095mm - 11765lm **Anodized Grey**
- N10U303U14.DA 3095mm - 11765lm **Black**
- N10UFC3U30.DA Flat Corner - 4278lm **White**
- N10UFC3U02.DA Flat Corner - 4278lm **Anodized Grey**
- N10UFC3U14.DA Flat Corner - 4278lm **Black**
- N10UEM3U30.DA Emergency - 5348lm **White**
- N10UEM3U02.DA Emergency - 5348lm **Anodized Grey**
- N10UEM3U14.DA Emergency - 5348lm **Black**
- N10U083U30.DA 845mm - 3208lm **White**
- N10U083U02.DA 845mm - 3208lm **Anodized Grey**
- N10U083U14.DA 845mm - 3208lm **Black**
- N10U163U30.DA 1690mm - 6417lm **White**
- N10U163U02.DA 1690mm - 6417lm **Anodized Grey**
- N10U163U14.DA 1690mm - 6417lm **Black**
- N10U253U30.DA 2530mm - 9626lm **White**
- N10U253U02.DA 2530mm - 9626lm **Anodized Grey**
- N10U253U14.DA 2530mm - 9626lm **Black**



In-Finity 100 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali . Accessories


Electrical



08.0031.00.DA

Power supply rose. Dali

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable



In-Finity 100 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

In-Finity 100 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali . Lamp



Top LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Top LED

- N10U113U30.DA 1125mm - 4278lm White
- N10U113U02.DA 1125mm - 4278lm Anodized Grey
- N10U113U14.DA 1125mm - 4278lm Black
- N10U143U30.DA 1405mm - 5348lm White
- N10U143U02.DA 1405mm - 5348lm Anodized Grey
- N10U143U14.DA 1405mm - 5348lm Black
- N10U193U30.DA 1970mm - 7487lm White
- N10U193U02.DA 1970mm - 7487lm Anodized Grey
- N10U193U14.DA 1970mm - 7487lm Black
- N10U303U30.DA 3095mm - 11765lm White
- N10U303U02.DA 3095mm - 11765lm Anodized Grey
- N10U303U14.DA 3095mm - 11765lm Black
- N10UFC3U30.DA Flat Corner - 4278lm White
- N10UFC3U02.DA Flat Corner - 4278lm Anodized Grey
- N10UFC3U14.DA Flat Corner - 4278lm Black
- N10UEM3U30.DA Emergency - 5348lm White
- N10UEM3U02.DA Emergency - 5348lm Anodized Grey
- N10UEM3U14.DA Emergency - 5348lm Black
- N10U083U30.DA 845mm - 3208lm White
- N10U083U02.DA 845mm - 3208lm Anodized Grey
- N10U083U14.DA 845mm - 3208lm Black
- N10U163U30.DA 1690mm - 6417lm White
- N10U163U02.DA 1690mm - 6417lm Anodized Grey
- N10U163U14.DA 1690mm - 6417lm Black
- N10U253U30.DA 2530mm - 9626lm White
- N10U253U02.DA 2530mm - 9626lm Anodized Grey
- N10U253U14.DA 2530mm - 9626lm Black

