


IN-FINITY 100 SUSPENSION UP & DOWN 4000K MICRO-PRISMATIC DIFFUSER

Number of heads	1
Mounting	Pendant up & down
Lamps description	Top LED 46,9W/m 4000K CRI 80 1680 lm/m UP - 4228 lm/m DOWN
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Suspension Up & Down 4000K Micro-Prismatic Diffuser

designed by FLOS Architectural

OPTICAL

Aiming	Fixed
Light distribution symmetry	Direct - Indirect
Beam angle	77°

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.


ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic
Emergency	Without
Insulation class	Class I

- N10U114U30 1125mm - 4331lm White
- N10U114U02 1125mm - 4331lm Anodized Grey
- N10U114U14 1125mm - 4331lm Black
- N10U144U30 1405mm - 5414lm White
- N10U144U02 1405mm - 5414lm Anodized Grey
- N10U144U14 1405mm - 5414lm Black
- N10U194U30 1970mm - 7580lm White
- N10U194U02 1970mm - 7580lm Anodized Grey
- N10U194U14 1970mm - 7580lm Black
- N10U304U30 3095mm - 11912lm White
- N10U304U02 3095mm - 11912lm Anodized Grey
- N10U304U14 3095mm - 11912lm Black
- N10UFC4U30 Flat Corner - 4331lm White
- N10UFC4U02 Flat Corner - 4331lm Anodized Grey
- N10UFC4U14 Flat Corner - 4331lm Black
- N10UEM4U30 Emergency - 5414lm White
- N10UEM4U02 Emergency - 5414lm Anodized Grey
- N10UEM4U14 Emergency - 5414lm Black
- N10U084U30 845mm - 3248lm White
- N10U084U02 845mm - 3248lm Anodized Grey
- N10U084U14 845mm - 3248lm Black
- N10U164U30 1690mm - 6497lm White
- N10U164U02 1690mm - 6497lm Anodized Grey
- N10U164U14 1690mm - 6497lm Black
- N10U254U30 2530mm - 9746lm White
- N10U254U02 2530mm - 9746lm Anodized Grey
- N10U254U14 2530mm - 9746lm Black

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



In-Finity 100 Suspension Up & Down 4000K Micro-Prismatic Diffuser . Accessories


Structural



- 08.9058.40
- 08.9058.02
- 08.9058.NS
- 08.9058.06

Metal cover. Suspension Up & Down. 100 mm

Metal cover for the different profiles. 2 unit kit.



In-Finity 100 Suspension Up & Down 4000K Micro-Prismatic Diffuser

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N10U114U30 1125mm - 433lm White
- N10U114U02 1125mm - 433lm Anodized Grey
- N10U114U14 1125mm - 433lm Black
- N10U144U30 1405mm - 5414lm White
- N10U144U02 1405mm - 5414lm Anodized Grey
- N10U144U14 1405mm - 5414lm Black
- N10U194U30 1970mm - 7580lm White
- N10U194U02 1970mm - 7580lm Anodized Grey
- N10U194U14 1970mm - 7580lm Black
- N10U304U30 3095mm - 11912lm White
- N10U304U02 3095mm - 11912lm Anodized Grey
- N10U304U14 3095mm - 11912lm Black
- N10UFC4U30 Flat Corner - 433lm White
- N10UFC4U02 Flat Corner - 433lm Anodized Grey
- N10UFC4U14 Flat Corner - 433lm Black
- N10UEM4U30 Emergency - 5414lm White
- N10UEM4U02 Emergency - 5414lm Anodized Grey
- N10UEM4U14 Emergency - 5414lm Black
- N10U084U30 845mm - 3248lm White
- N10U084U02 845mm - 3248lm Anodized Grey
- N10U084U14 845mm - 3248lm Black
- N10U164U30 1690mm - 6497lm White
- N10U164U02 1690mm - 6497lm Anodized Grey
- N10U164U14 1690mm - 6497lm Black
- N10U254U30 2530mm - 9746lm White
- N10U254U02 2530mm - 9746lm Anodized Grey
- N10U254U14 2530mm - 9746lm Black

Mounting



- 08.0030

Suspension kit

One unit Suspension kit (L = 4 m).
Maximum distance between the suspension cables: 2 m.



In-Finity 100 Suspension Up & Down 4000K Micro-Prismatic Diffuser . Accessories

Electrical



08.0031.00

Power supply rose

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable

In-Finity 100 Suspension Up & Down 4000K Micro-Prismatic Diffuser . Lamps



Top LED

Lamp category:


LED

Socket:

Special base

Lamp type:

Top LED



In-Finity 100 Suspension Up & Down 4000K Micro-Prismatic Diffuser

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N10U114U30 1125mm - 433lm White
- N10U114U02 1125mm - 433lm Anodized Grey
- N10U114U14 1125mm - 433lm Black
- N10U144U30 1405mm - 5414lm White
- N10U144U02 1405mm - 5414lm Anodized Grey
- N10U144U14 1405mm - 5414lm Black
- N10U194U30 1970mm - 7580lm White
- N10U194U02 1970mm - 7580lm Anodized Grey
- N10U194U14 1970mm - 7580lm Black
- N10U304U30 3095mm - 11912lm White
- N10U304U02 3095mm - 11912lm Anodized Grey
- N10U304U14 3095mm - 11912lm Black
- N10UFC4U30 Flat Corner - 433lm White
- N10UFC4U02 Flat Corner - 433lm Anodized Grey
- N10UFC4U14 Flat Corner - 433lm Black
- N10UEM4U30 Emergency - 5414lm White
- N10UEM4U02 Emergency - 5414lm Anodized Grey
- N10UEM4U14 Emergency - 5414lm Black
- N10U084U30 845mm - 3248lm White
- N10U084U02 845mm - 3248lm Anodized Grey
- N10U084U14 845mm - 3248lm Black
- N10U164U30 1690mm - 6497lm White
- N10U164U02 1690mm - 6497lm Anodized Grey
- N10U164U14 1690mm - 6497lm Black
- N10U254U30 2530mm - 9746lm White
- N10U254U02 2530mm - 9746lm Anodized Grey
- N10U254U14 2530mm - 9746lm Black

