


IN-FINITY 100 SUSPENSION UP & DOWN 4000K MICRO-PRISMATIC DIFFUSER DALI

Number of heads	1
Mounting	Pendant up & down
Lamps description	Top LED 46,9W/m 4000K CRI 80 1680 lm/m UP - 4228 lm/m DOWN
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Suspension Up & Down 4000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

OPTICAL

Aiming	Fixed
Light distribution symmetry	Direct - Indirect
Beam angle	77°

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.


ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic dimmable dali
Emergency	Without
Insulation class	Class I

- N10U114U30.DA 1125mm - 4331lm **White**
- N10U114U02.DA 1125mm - 4331lm **Anodized Grey**
- N10U114U14.DA 1125mm - 4331lm **Black**
- N10U144U30.DA 1405mm - 5414lm **White**
- N10U144U02.DA 1405mm - 5414lm **Anodized Grey**
- N10U144U14.DA 1405mm - 5414lm **Black**
- N10U194U30.DA 1970mm - 7580lm **White**
- N10U194U02.DA 1970mm - 7580lm **Anodized Grey**
- N10U194U14.DA 1970mm - 7580lm **Black**
- N10U304U30.DA 3095mm - 11912lm **White**
- N10U304U02.DA 3095mm - 11912lm **Anodized Grey**
- N10U304U14.DA 3095mm - 11912lm **Black**
- N10UFC4U30.DA Flat Corner - 4331lm **White**
- N10UFC4U02.DA Flat Corner - 4331lm **Anodized Grey**
- N10UFC4U14.DA Flat Corner - 4331lm **Black**
- N10UEM4U30.DA Emergency - 5414lm **White**
- N10UEM4U02.DA Emergency - 5414lm **Anodized Grey**
- N10UEM4U14.DA Emergency - 5414lm **Black**
- N10U084U30.DA 845mm - 3248lm **White**
- N10U084U02.DA 845mm - 3248lm **Anodized Grey**
- N10U084U14.DA 845mm - 3248lm **Black**
- N10U164U30.DA 1690mm - 6497lm **White**
- N10U164U02.DA 1690mm - 6497lm **Anodized Grey**
- N10U164U14.DA 1690mm - 6497lm **Black**
- N10U254U30.DA 2530mm - 9746lm **White**
- N10U254U02.DA 2530mm - 9746lm **Anodized Grey**
- N10U254U14.DA 2530mm - 9746lm **Black**

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



In-Finity 100 Suspension Up & Down 4000K Micro-Prismatic Diffuser Dali . Accessories

Structural



- 08.9058.40
- 08.9058.02
- 08.9058.NS
- 08.9058.06

Metal cover. Suspension Up & Down. 100 mm

Metal cover for the different profiles. 2 unit kit.


Mounting



- 08.0030

Suspension kit

One unit Suspension kit (L = 4 m).
Maximum distance between the suspension cables: 2 m.



In-Finity 100 Suspension Up & Down 4000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N10U114U30.DA 1125mm - 4331lm **White**
- N10U114U02.DA 1125mm - 4331lm **Anodized Grey**
- N10U114U14.DA 1125mm - 4331lm **Black**
- N10U144U30.DA 1405mm - 5414lm **White**
- N10U144U02.DA 1405mm - 5414lm **Anodized Grey**
- N10U144U14.DA 1405mm - 5414lm **Black**
- N10U194U30.DA 1970mm - 7580lm **White**
- N10U194U02.DA 1970mm - 7580lm **Anodized Grey**
- N10U194U14.DA 1970mm - 7580lm **Black**
- N10U304U30.DA 3095mm - 11912lm **White**
- N10U304U02.DA 3095mm - 11912lm **Anodized Grey**
- N10U304U14.DA 3095mm - 11912lm **Black**
- N10UFC4U30.DA Flat Corner - 4331lm **White**
- N10UFC4U02.DA Flat Corner - 4331lm **Anodized Grey**
- N10UFC4U14.DA Flat Corner - 4331lm **Black**
- N10UJEM4U30.DA Emergency - 5414lm **White**
- N10UJEM4U02.DA Emergency - 5414lm **Anodized Grey**
- N10UJEM4U14.DA Emergency - 5414lm **Black**
- N10U084U30.DA 845mm - 3248lm **White**
- N10U084U02.DA 845mm - 3248lm **Anodized Grey**
- N10U084U14.DA 845mm - 3248lm **Black**
- N10U164U30.DA 1690mm - 6497lm **White**
- N10U164U02.DA 1690mm - 6497lm **Anodized Grey**
- N10U164U14.DA 1690mm - 6497lm **Black**
- N10U254U30.DA 2530mm - 9746lm **White**
- N10U254U02.DA 2530mm - 9746lm **Anodized Grey**
- N10U254U14.DA 2530mm - 9746lm **Black**



In-Finity 100 Suspension Up & Down 4000K Micro-Prismatic Diffuser Dali . Accessories


Electrical



08.0031.00.DA

Power supply rose. Dali

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable



In-Finity 100 Suspension Up & Down 4000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

In-Finity 100 Suspension Up & Down 4000K Micro-Prismatic Diffuser Dali . Lamp



Top LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Top LED

- N10U114U30.DA 1125mm - 4331lm White
- N10U114U02.DA 1125mm - 4331lm Anodized Grey
- N10U114U14.DA 1125mm - 4331lm Black
- N10U144U30.DA 1405mm - 5414lm White
- N10U144U02.DA 1405mm - 5414lm Anodized Grey
- N10U144U14.DA 1405mm - 5414lm Black
- N10U194U30.DA 1970mm - 7580lm White
- N10U194U02.DA 1970mm - 7580lm Anodized Grey
- N10U194U14.DA 1970mm - 7580lm Black
- N10U304U30.DA 3095mm - 11912lm White
- N10U304U02.DA 3095mm - 11912lm Anodized Grey
- N10U304U14.DA 3095mm - 11912lm Black
- N10UFC4U30.DA Flat Corner - 4331lm White
- N10UFC4U02.DA Flat Corner - 4331lm Anodized Grey
- N10UFC4U14.DA Flat Corner - 4331lm Black
- N10UEM4U30.DA Emergency - 5414lm White
- N10UEM4U02.DA Emergency - 5414lm Anodized Grey
- N10UEM4U14.DA Emergency - 5414lm Black
- N10U084U30.DA 845mm - 3248lm White
- N10U084U02.DA 845mm - 3248lm Anodized Grey
- N10U084U14.DA 845mm - 3248lm Black
- N10U164U30.DA 1690mm - 6497lm White
- N10U164U02.DA 1690mm - 6497lm Anodized Grey
- N10U164U14.DA 1690mm - 6497lm Black
- N10U254U30.DA 2530mm - 9746lm White
- N10U254U02.DA 2530mm - 9746lm Anodized Grey
- N10U254U14.DA 2530mm - 9746lm Black

