

IN-FINITY 35 RECESSED TRIM 4000K MICRO-PRISMATIC DIFFUSER

Number of heads	1
Mounting	Recessed Trim
Lamps description	Top LED 19,8W/m 2761 lm/m 4000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1400 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

OPTICAL


Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	76°

ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic
Emergency	Without
Insulation class	Class I

PHYSICAL

Recessed depth (mm)	120
Construction material	Aluminium



In-Finity 35 Recessed Trim 4000K Micro-Prismatic Diffuser

designed by FLOS Architectural

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

- N35T054U30B 565mm - 553lm White
- N35T054U02B 565mm - 553lm Anodized Grey
- N35T054U14B 565mm - 553lm Black
- N35T084U30B 845mm - 830lm White
- N35T084U02B 845mm - 830lm Anodized Grey
- N35T084U14B 845mm - 830lm Black
- N35T114U30B 1125mm - 1107lm White
- N35T114U02B 1125mm - 1107lm Anodized Grey
- N35T114U14B 1125mm - 1107lm Black
- N35T144U30B 1405mm - 1384lm White
- N35T144U02B 1405mm - 1384lm Anodized Grey
- N35T144U14B 1405mm - 1384lm Black
- N35T164U30B 1690mm - 1660lm White
- N35T164U02B 1690mm - 1660lm Anodized Grey
- N35T164U14B 1690mm - 1660lm Black
- N35T194U30B 1970mm - 1937lm White
- N35T194U02B 1970mm - 1937lm Anodized Grey
- N35T194U14B 1970mm - 1937lm Black
- N35T254U30B 2530mm - 2491lm White
- N35T254U02B 2530mm - 2491lm Anodized Grey
- N35T254U14B 2530mm - 2491lm Black
- N35T304U30B 3095mm - 3044lm White
- N35T304U02B 3095mm - 3044lm Anodized Grey
- N35T304U14B 3095mm - 3044lm Black
- N35TFC4U30B Flat Corner - 1107lm White
- N35TFC4U02B Flat Corner - 1107lm Anodized Grey
- N35TFC4U14B Flat Corner - 1107lm Black
- N35TDC4U30B Dihedral Corner - 1107lm White
- N35TDC4U02B Dihedral Corner - 1107lm Anodized Grey
- N35TDC4U14B Dihedral Corner - 1107lm Black
- N35TEM4U30B Emergency - 1384lm White
- N35TEM4U02B Emergency - 1384lm Anodized Grey
- N35TEM4U14B Emergency - 1384lm Black



In-Finity 35 Recessed Trim 4000K Micro-Prismatic Diffuser . Accessories


Structural



- 08.9051.40
- 08.9051.02
- 08.9051.NS

Metal cover. Recessed Trim. 35 mm

Metal cover for the different profiles. 2 unit kit.



In-Finity 35 Recessed Trim 4000K Micro-Prismatic Diffuser designed by FLOS Architectural

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

In-Finity 35 Recessed Trim 4000K Micro-Prismatic Diffuser . Lamps



Top LED

Lamp category:
LED

Socket:
Special base

Lamp type:
Top LED

- N35T054U30B 565mm - 553lm White
- N35T054U02B 565mm - 553lm Anodized Grey
- N35T054U14B 565mm - 553lm Black
- N35T084U30B 845mm - 830lm White
- N35T084U02B 845mm - 830lm Anodized Grey
- N35T084U14B 845mm - 830lm Black
- N35T114U30B 1125mm - 1107lm White
- N35T114U02B 1125mm - 1107lm Anodized Grey
- N35T114U14B 1125mm - 1107lm Black
- N35T144U30B 1405mm - 1384lm White
- N35T144U02B 1405mm - 1384lm Anodized Grey
- N35T144U14B 1405mm - 1384lm Black
- N35T164U30B 1690mm - 1660lm White
- N35T164U02B 1690mm - 1660lm Anodized Grey
- N35T164U14B 1690mm - 1660lm Black
- N35T194U30B 1970mm - 1937lm White
- N35T194U02B 1970mm - 1937lm Anodized Grey
- N35T194U14B 1970mm - 1937lm Black
- N35T254U30B 2530mm - 2491lm White
- N35T254U02B 2530mm - 2491lm Anodized Grey
- N35T254U14B 2530mm - 2491lm Black
- N35T304U30B 3095mm - 3044lm White
- N35T304U02B 3095mm - 3044lm Anodized Grey
- N35T304U14B 3095mm - 3044lm Black
- N35TFC4U30B Flat Corner - 1107lm White
- N35TFC4U02B Flat Corner - 1107lm Anodized Grey
- N35TFC4U14B Flat Corner - 1107lm Black
- N35TDC4U30B Dihedral Corner - 1107lm White
- N35TDC4U02B Dihedral Corner - 1107lm Anodized Grey
- N35TDC4U14B Dihedral Corner - 1107lm Black
- N35TEM4U30B Emergency - 1384lm White
- N35TEM4U02B Emergency - 1384lm Anodized Grey
- N35TEM4U14B Emergency - 1384lm Black