


## IN-FINITY 35 SUSPENSION UP & DOWN 3000K GENERAL LIGHTING DALI

<b>Number of heads</b>	1
<b>Mounting</b>	Pendant up & down
<b>Lamps description</b>	Top LED 32,6W/m 3000K CRI 80 1536 lm/m UP - 2558 lm/m DOWN
<b>Luminaire luminous flux</b>	See reference number
<b>Voltage (V)</b>	220/240
<b>Environment</b>	Indoor
<b>Notes</b>	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1400 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



**In-Finity 35 Suspension Up & Down 3000K General Lighting Dali**  
designed by FLOS Architectural

### OPTICAL

<b>Aiming</b>	Fixed
<b>Light distribution symmetry</b>	Direct - Indirect
<b>Beam angle</b>	110°

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.


### ELECTRICAL

<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Integral
<b>Transformer type</b>	Electronic dimmable dali
<b>Emergency</b>	Without
<b>Insulation class</b>	Class I

- N35U113G30BDA 1125mm - 2130lm **White**
- N35U113G02BDA 1125mm - 2130lm **Anodized Grey**
- N35U113G14BDA 1125mm - 2130lm **Black**
- N35U143G30BDA 1405mm - 2663lm **White**
- N35U143G02BDA 1405mm - 2663lm **Anodized Grey**
- N35U143G14BDA 1405mm - 2663lm **Black**
- N35U193G30BDA 1970mm - 3728lm **White**
- N35U193G02BDA 1970mm - 3728lm **Anodized Grey**
- N35U193G14BDA 1970mm - 3728lm **Black**
- N35U303G30BDA 3095mm - 5858lm **White**
- N35U303G02BDA 3095mm - 5858lm **Anodized Grey**
- N35U303G14BDA 3095mm - 5858lm **Black**
- N35UFC3G30BDA Flat Corner - 2130lm **White**
- N35UFC3G02BDA Flat Corner - 2130lm **Anodized Grey**
- N35UFC3G14BDA Flat Corner - 2130lm **Black**
- N35UEM3G30BDA Emergency - 2663lm **White**
- N35UEM3G02BDA Emergency - 2663lm **Anodized Grey**
- N35UEM3G14BDA Emergency - 2663lm **Black**
- N35U083G30BDA 845mm - 1598lm **White**
- N35U083G02BDA 845mm - 1598lm **Anodized Grey**
- N35U083G14BDA 845mm - 1598lm **Black**
- N35U163G30BDA 1690mm - 3195lm **White**
- N35U163G02BDA 1690mm - 3195lm **Anodized Grey**
- N35U163G14BDA 1690mm - 3195lm **Black**
- N35U253G30BDA 2530mm - 4793lm **White**
- N35U253G02BDA 2530mm - 4793lm **Anodized Grey**
- N35U253G14BDA 2530mm - 4793lm **Black**

### PHYSICAL

<b>Construction material</b>	Aluminium
------------------------------	-----------



## In-Finity 35 Suspension Up & Down 3000K General Lighting Dali . Accessories

### Structural



- 08.9056.40
- 08.9056.02
- 08.9056.NS
- 08.9056.06

#### Metal cover. Suspension Up & Down. 35 mm

Metal cover for the different profiles. 2 unit kit.


### Mounting



- 08.0030

#### Suspension kit

One unit Suspension kit (L = 4 m).  
Maximum distance between the suspension cables: 2 m.



### In-Finity 35 Suspension Up & Down 3000K General Lighting Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N35U113G30BDA 1125mm - 2130lm **White**
- N35U113G02BDA 1125mm - 2130lm **Anodized Grey**
- N35U113G14BDA 1125mm - 2130lm **Black**
- N35U143G30BDA 1405mm - 2663lm **White**
- N35U143G02BDA 1405mm - 2663lm **Anodized Grey**
- N35U143G14BDA 1405mm - 2663lm **Black**
- N35U193G30BDA 1970mm - 3728lm **White**
- N35U193G02BDA 1970mm - 3728lm **Anodized Grey**
- N35U193G14BDA 1970mm - 3728lm **Black**
- N35U303G30BDA 3095mm - 5858lm **White**
- N35U303G02BDA 3095mm - 5858lm **Anodized Grey**
- N35U303G14BDA 3095mm - 5858lm **Black**
- N35UFC3G30BDA Flat Corner - 2130lm **White**
- N35UFC3G02BDA Flat Corner - 2130lm **Anodized Grey**
- N35UFC3G14BDA Flat Corner - 2130lm **Black**
- N35UEM3G30BDA Emergency - 2663lm **White**
- N35UEM3G02BDA Emergency - 2663lm **Anodized Grey**
- N35UEM3G14BDA Emergency - 2663lm **Black**
- N35U083G30BDA 845mm - 1598lm **White**
- N35U083G02BDA 845mm - 1598lm **Anodized Grey**
- N35U083G14BDA 845mm - 1598lm **Black**
- N35U163G30BDA 1690mm - 3195lm **White**
- N35U163G02BDA 1690mm - 3195lm **Anodized Grey**
- N35U163G14BDA 1690mm - 3195lm **Black**
- N35U253G30BDA 2530mm - 4793lm **White**
- N35U253G02BDA 2530mm - 4793lm **Anodized Grey**
- N35U253G14BDA 2530mm - 4793lm **Black**



## In-Finity 35 Suspension Up & Down 3000K General Lighting Dali . Accessories

### Electrical



08.0031.00.DA

#### Power supply rose. Dali

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable

## In-Finity 35 Suspension Up & Down 3000K General Lighting Dali . Lamps



#### Top LED

#### Lamp category:


LED

#### Socket:

Special base

#### Lamp type:

Top LED



## In-Finity 35 Suspension Up & Down 3000K General Lighting Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N35U113G30BDA 1125mm - 2130lm White
- N35U113G02BDA 1125mm - 2130lm Anodized Grey
- N35U113G14BDA 1125mm - 2130lm Black
- N35U143G30BDA 1405mm - 2663lm White
- N35U143G02BDA 1405mm - 2663lm Anodized Grey
- N35U143G14BDA 1405mm - 2663lm Black
- N35U193G30BDA 1970mm - 3728lm White
- N35U193G02BDA 1970mm - 3728lm Anodized Grey
- N35U193G14BDA 1970mm - 3728lm Black
- N35U303G30BDA 3095mm - 5858lm White
- N35U303G02BDA 3095mm - 5858lm Anodized Grey
- N35U303G14BDA 3095mm - 5858lm Black
- N35UFC3G30BDA Flat Corner - 2130lm White
- N35UFC3G02BDA Flat Corner - 2130lm Anodized Grey
- N35UFC3G14BDA Flat Corner - 2130lm Black
- N35UEM3G30BDA Emergency - 2663lm White
- N35UEM3G02BDA Emergency - 2663lm Anodized Grey
- N35UEM3G14BDA Emergency - 2663lm Black
- N35U083G30BDA 845mm - 1598lm White
- N35U083G02BDA 845mm - 1598lm Anodized Grey
- N35U083G14BDA 845mm - 1598lm Black
- N35U163G30BDA 1690mm - 3195lm White
- N35U163G02BDA 1690mm - 3195lm Anodized Grey
- N35U163G14BDA 1690mm - 3195lm Black
- N35U253G30BDA 2530mm - 4793lm White
- N35U253G02BDA 2530mm - 4793lm Anodized Grey
- N35U253G14BDA 2530mm - 4793lm Black

