


## IN-FINITY 35 SUSPENSION UP & DOWN 3000K MICRO-PRISMATIC DIFFUSER DALI

<b>Number of heads</b>	1
<b>Mounting</b>	Pendant up & down
<b>Lamps description</b>	Top LED 32,6W/m 3000K CRI 80 1536 lm/m UP - 2558 lm/m DOWN
<b>Luminaire luminous flux</b>	See reference number
<b>Voltage (V)</b>	220/240
<b>Environment</b>	Indoor
<b>Notes</b>	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1400 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



### In-Finity 35 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

### OPTICAL

<b>Aiming</b>	Fixed
<b>Light distribution symmetry</b>	Direct - Indirect
<b>Beam angle</b>	76°

### ELECTRICAL


<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Integral
<b>Transformer type</b>	Electronic dimmable dali
<b>Emergency</b>	Without
<b>Insulation class</b>	Class I

### PHYSICAL

<b>Construction material</b>	Aluminium
------------------------------	-----------



- N35U113U30BDA 1125mm - 1838lm White
- N35U113U02BDA 1125mm - 1838lm Anodized Grey
- N35U113U14BDA 1125mm - 1838lm Black
- N35U143U30BDA 1405mm - 2297lm White
- N35U143U02BDA 1405mm - 2297lm Anodized Grey
- N35U143U14BDA 1405mm - 2297lm Black
- N35U193U30BDA 1970mm - 3216lm White
- N35U193U02BDA 1970mm - 3216lm Anodized Grey
- N35U193U14BDA 1970mm - 3216lm Black
- N35U303U30BDA 3095mm - 5054lm White
- N35U303U02BDA 3095mm - 5054lm Anodized Grey
- N35U303U14BDA 3095mm - 5054lm Black
- N35UFC3U30BDA Flat Corner - 1838lm White
- N35UFC3U02BDA Flat Corner - 1838lm Anodized Grey
- N35UFC3U14BDA Flat Corner - 1838lm Black
- N35UEM3U30BDA Emergency - 2297lm White
- N35UEM3U02BDA Emergency - 2297lm Anodized Grey
- N35UEM3U14BDA Emergency - 2297lm Black
- N35U083U30BDA 845mm - 1378lm White
- N35U083U02BDA 845mm - 1378lm Anodized Grey
- N35U083U14BDA 845mm - 1378lm Black
- N35U163U30BDA 1690mm - 2757lm White
- N35U163U02BDA 1690mm - 2757lm Anodized Grey
- N35U163U14BDA 1690mm - 2757lm Black
- N35U253U30BDA 2530mm - 4135lm White
- N35U253U02BDA 2530mm - 4135lm Anodized Grey
- N35U253U14BDA 2530mm - 4135lm Black



## In-Finity 35 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali . Accessories

### Structural




- 08.9056.40
- 08.9056.02
- 08.9056.NS
- 08.9056.06

#### Metal cover. Suspension Up & Down. 35 mm

Metal cover for the different profiles. 2 unit kit.


### Mounting



- 08.0030

#### Suspension kit

One unit Suspension kit (L = 4 m).  
Maximum distance between the suspension cables: 2 m.




### In-Finity 35 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N35U113U30BDA 1125mm - 1838lm **White**
- N35U113U02BDA 1125mm - 1838lm **Anodized Grey**
- N35U113U14BDA 1125mm - 1838lm **Black**
- N35U143U30BDA 1405mm - 2297lm **White**
- N35U143U02BDA 1405mm - 2297lm **Anodized Grey**
- N35U143U14BDA 1405mm - 2297lm **Black**
- N35U193U30BDA 1970mm - 3216lm **White**
- N35U193U02BDA 1970mm - 3216lm **Anodized Grey**
- N35U193U14BDA 1970mm - 3216lm **Black**
- N35U303U30BDA 3095mm - 5054lm **White**
- N35U303U02BDA 3095mm - 5054lm **Anodized Grey**
- N35U303U14BDA 3095mm - 5054lm **Black**
- N35UFC3U30BDA Flat Corner - 1838lm **White**
- N35UFC3U02BDA Flat Corner - 1838lm **Anodized Grey**
- N35UFC3U14BDA Flat Corner - 1838lm **Black**
- N35UEM3U30BDA Emergency - 2297lm **White**
- N35UEM3U02BDA Emergency - 2297lm **Anodized Grey**
- N35UEM3U14BDA Emergency - 2297lm **Black**
- N35U083U30BDA 845mm - 1378lm **White**
- N35U083U02BDA 845mm - 1378lm **Anodized Grey**
- N35U083U14BDA 845mm - 1378lm **Black**
- N35U163U30BDA 1690mm - 2757lm **White**
- N35U163U02BDA 1690mm - 2757lm **Anodized Grey**
- N35U163U14BDA 1690mm - 2757lm **Black**
- N35U253U30BDA 2530mm - 4135lm **White**
- N35U253U02BDA 2530mm - 4135lm **Anodized Grey**
- N35U253U14BDA 2530mm - 4135lm **Black**



## In-Finity 35 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali . Accessories


### Electrical



08.0031.00.DA

#### Power supply rose. Dali

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable



### In-Finity 35 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

## In-Finity 35 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali . Lamps



#### Top LED

#### Lamp category:

LED

#### Socket:

Special base

#### Lamp type:

Top LED

- N35U113U30BDA 1125mm - 1838lm White
- N35U113U02BDA 1125mm - 1838lm Anodized Grey
- N35U113U14BDA 1125mm - 1838lm Black
- N35U143U30BDA 1405mm - 2297lm White
- N35U143U02BDA 1405mm - 2297lm Anodized Grey
- N35U143U14BDA 1405mm - 2297lm Black
- N35U193U30BDA 1970mm - 3216lm White
- N35U193U02BDA 1970mm - 3216lm Anodized Grey
- N35U193U14BDA 1970mm - 3216lm Black
- N35U303U30BDA 3095mm - 5054lm White
- N35U303U02BDA 3095mm - 5054lm Anodized Grey
- N35U303U14BDA 3095mm - 5054lm Black
- N35UFC3U30BDA Flat Corner - 1838lm White
- N35UFC3U02BDA Flat Corner - 1838lm Anodized Grey
- N35UFC3U14BDA Flat Corner - 1838lm Black
- N35UEM3U30BDA Emergency - 2297lm White
- N35UEM3U02BDA Emergency - 2297lm Anodized Grey
- N35UEM3U14BDA Emergency - 2297lm Black
- N35U083U30BDA 845mm - 1378lm White
- N35U083U02BDA 845mm - 1378lm Anodized Grey
- N35U083U14BDA 845mm - 1378lm Black
- N35U163U30BDA 1690mm - 2757lm White
- N35U163U02BDA 1690mm - 2757lm Anodized Grey
- N35U163U14BDA 1690mm - 2757lm Black
- N35U253U30BDA 2530mm - 4135lm White
- N35U253U02BDA 2530mm - 4135lm Anodized Grey
- N35U253U14BDA 2530mm - 4135lm Black

