


IN-FINITY 35 SUSPENSION UP & DOWN 4000K MICRO-PRISMATIC DIFFUSER DALI

Number of heads	1
Mounting	Pendant up & down
Lamps description	Top LED 32,6W/m 4000K CRI 80 1680 lm/m UP - 2761 lm/m DOWN
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1400 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 35 Suspension Up & Down 4000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

OPTICAL

Aiming	Fixed
Light distribution symmetry	Direct - Indirect
Beam angle	76°

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.


ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic dimmable dali
Emergency	Without
Insulation class	Class I

- N35U114U30BDA 1125mm - 1990lm **White**
- N35U114U02BDA 1125mm - 1990lm **Anodized Grey**
- N35U114U14BDA 1125mm - 1990lm **Black**
- N35U144U30BDA 1405mm - 2487lm **White**
- N35U144U02BDA 1405mm - 2487lm **Anodized Grey**
- N35U144U14BDA 1405mm - 2487lm **Black**
- N35U194U30BDA 1970mm - 3482lm **White**
- N35U194U02BDA 1970mm - 3482lm **Anodized Grey**
- N35U194U14BDA 1970mm - 3482lm **Black**
- N35U304U30BDA 3095mm - 5472lm **White**
- N35U304U02BDA 3095mm - 5472lm **Anodized Grey**
- N35U304U14BDA 3095mm - 5472lm **Black**
- N35UFC4U30BDA Flat Corner - 1990lm **White**
- N35UFC4U02BDA Flat Corner - 1990lm **Anodized Grey**
- N35UFC4U14BDA Flat Corner - 1990lm **Black**
- N35UEM4U30BDA Emergency - 2487lm **White**
- N35UEM4U02BDA Emergency - 2487lm **Anodized Grey**
- N35UEM4U14BDA Emergency - 2487lm **Black**
- N35U084U30BDA 845mm - 1492lm **White**
- N35U084U02BDA 845mm - 1492lm **Anodized Grey**
- N35U084U14BDA 845mm - 1492lm **Black**
- N35U164U30BDA 1690mm - 2985lm **White**
- N35U164U02BDA 1690mm - 2985lm **Anodized Grey**
- N35U164U14BDA 1690mm - 2985lm **Black**
- N35U254U30BDA 2530mm - 4477lm **White**
- N35U254U02BDA 2530mm - 4477lm **Anodized Grey**
- N35U254U14BDA 2530mm - 4477lm **Black**

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



In-Finity 35 Suspension Up & Down 4000K Micro-Prismatic Diffuser Dali . Accessories

Structural




- 08.9056.40
- 08.9056.02
- 08.9056.NS
- 08.9056.06

Metal cover. Suspension Up & Down. 35 mm

Metal cover for the different profiles. 2 unit kit.


Mounting



- 08.0030

Suspension kit

One unit Suspension kit (L = 4 m).
Maximum distance between the suspension cables: 2 m.



In-Finity 35 Suspension Up & Down 4000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N35U114U30BDA 1125mm - 1990lm **White**
- N35U114U02BDA 1125mm - 1990lm **Anodized Grey**
- N35U114U14BDA 1125mm - 1990lm **Black**
- N35U144U30BDA 1405mm - 2487lm **White**
- N35U144U02BDA 1405mm - 2487lm **Anodized Grey**
- N35U144U14BDA 1405mm - 2487lm **Black**
- N35U194U30BDA 1970mm - 3482lm **White**
- N35U194U02BDA 1970mm - 3482lm **Anodized Grey**
- N35U194U14BDA 1970mm - 3482lm **Black**
- N35U304U30BDA 3095mm - 5472lm **White**
- N35U304U02BDA 3095mm - 5472lm **Anodized Grey**
- N35U304U14BDA 3095mm - 5472lm **Black**
- N35UFC4U30BDA Flat Corner - 1990lm **White**
- N35UFC4U02BDA Flat Corner - 1990lm **Anodized Grey**
- N35UFC4U14BDA Flat Corner - 1990lm **Black**
- N35UEM4U30BDA Emergency - 2487lm **White**
- N35UEM4U02BDA Emergency - 2487lm **Anodized Grey**
- N35UEM4U14BDA Emergency - 2487lm **Black**
- N35U084U30BDA 845mm - 1492lm **White**
- N35U084U02BDA 845mm - 1492lm **Anodized Grey**
- N35U084U14BDA 845mm - 1492lm **Black**
- N35U164U30BDA 1690mm - 2985lm **White**
- N35U164U02BDA 1690mm - 2985lm **Anodized Grey**
- N35U164U14BDA 1690mm - 2985lm **Black**
- N35U254U30BDA 2530mm - 4477lm **White**
- N35U254U02BDA 2530mm - 4477lm **Anodized Grey**
- N35U254U14BDA 2530mm - 4477lm **Black**



In-Finity 35 Suspension Up & Down 4000K Micro-Prismatic Diffuser Dali . Accessories


Electrical



08.0031.00.DA

Power supply rose. Dali

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable



In-Finity 35 Suspension Up & Down 4000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

In-Finity 35 Suspension Up & Down 4000K Micro-Prismatic Diffuser Dali . Lamps



Top LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Top LED

- N35U114U30BDA 1125mm - 1990lm White
- N35U114U02BDA 1125mm - 1990lm Anodized Grey
- N35U114U14BDA 1125mm - 1990lm Black
- N35U144U30BDA 1405mm - 2487lm White
- N35U144U02BDA 1405mm - 2487lm Anodized Grey
- N35U144U14BDA 1405mm - 2487lm Black
- N35U194U30BDA 1970mm - 3482lm White
- N35U194U02BDA 1970mm - 3482lm Anodized Grey
- N35U194U14BDA 1970mm - 3482lm Black
- N35U304U30BDA 3095mm - 5472lm White
- N35U304U02BDA 3095mm - 5472lm Anodized Grey
- N35U304U14BDA 3095mm - 5472lm Black
- N35UFC4U30BDA Flat Corner - 1990lm White
- N35UFC4U02BDA Flat Corner - 1990lm Anodized Grey
- N35UFC4U14BDA Flat Corner - 1990lm Black
- N35UEM4U30BDA Emergency - 2487lm White
- N35UEM4U02BDA Emergency - 2487lm Anodized Grey
- N35UEM4U14BDA Emergency - 2487lm Black
- N35U084U30BDA 845mm - 1492lm White
- N35U084U02BDA 845mm - 1492lm Anodized Grey
- N35U084U14BDA 845mm - 1492lm Black
- N35U164U30BDA 1690mm - 2985lm White
- N35U164U02BDA 1690mm - 2985lm Anodized Grey
- N35U164U14BDA 1690mm - 2985lm Black
- N35U254U30BDA 2530mm - 4477lm White
- N35U254U02BDA 2530mm - 4477lm Anodized Grey
- N35U254U14BDA 2530mm - 4477lm Black

