


IN-FINITY 70 SUSPENSION DOWN 3000K GENERAL LIGHTING

Number of heads	1
Mounting	Pendant
Lamps description	Top LED 23,1W/m 2877 lm/m 3000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1400 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 70 Suspension Down 3000K General Lighting

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	103°

ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic
Emergency	Without
Insulation class	Class I

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



- N70D053G30B 565mm - 1262lm White
- N70D053G02B 565mm - 1262lm Anodized Grey
- N70D053G14B 565mm - 1262lm Black
- N70D083G30B 845mm - 1893lm White
- N70D083G02B 845mm - 1893lm Anodized Grey
- N70D083G14B 845mm - 1893lm Black
- N70D113G30B 1125mm - 2524lm White
- N70D113G02B 1125mm - 2524lm Anodized Grey
- N70D113G14B 1125mm - 2524lm Black
- N70D143G30B 1405mm - 3155lm White
- N70D143G02B 1405mm - 3155lm Anodized Grey
- N70D143G14B 1405mm - 3155lm Black
- N70D163G30B 1690mm - 3786lm White
- N70D163G02B 1690mm - 3786lm Anodized Grey
- N70D163G14B 1690mm - 3786lm Black
- N70D193G30B 1970mm - 4417lm White
- N70D193G02B 1970mm - 4417lm Anodized Grey
- N70D193G14B 1970mm - 4417lm Black
- N70D253G30B 2530mm - 5680lm White
- N70D253G02B 2530mm - 5680lm Anodized Grey
- N70D253G14B 2530mm - 5680lm Black
- N70D303G30B 3095mm - 6942lm White
- N70D303G02B 3095mm - 6942lm Anodized Grey
- N70D303G14B 3095mm - 6942lm Black
- N70DFC3G30B Flat Corner - 2524lm White
- N70DFC3G02B Flat Corner - 2524lm Anodized Grey
- N70DFC3G14B Flat Corner - 2524lm Black
- N70DEM3G30B Emergency - 3155lm White
- N70DEM3G02B Emergency - 3155lm Anodized Grey
- N70DEM3G14B Emergency - 3155lm Black

In-Finity 70 Suspension Down 3000K General Lighting . Accessories


Structural



- 08.9052.40
- 08.9052.02
- 08.9052.NS
- 08.9052.06

Metal cover. Surface / Suspension Down. 70 mm

Metal cover for the different profiles. 2 unit kit.



In-Finity 70 Suspension Down 3000K General Lighting

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- N70D053G30B 565mm - 1262lm White
- N70D053G02B 565mm - 1262lm Anodized Grey
- N70D053G14B 565mm - 1262lm Black
- N70D083G30B 845mm - 1893lm White
- N70D083G02B 845mm - 1893lm Anodized Grey
- N70D083G14B 845mm - 1893lm Black
- N70D113G30B 1125mm - 2524lm White
- N70D113G02B 1125mm - 2524lm Anodized Grey
- N70D113G14B 1125mm - 2524lm Black
- N70D143G30B 1405mm - 3155lm White
- N70D143G02B 1405mm - 3155lm Anodized Grey
- N70D143G14B 1405mm - 3155lm Black
- N70D163G30B 1690mm - 3786lm White
- N70D163G02B 1690mm - 3786lm Anodized Grey
- N70D163G14B 1690mm - 3786lm Black
- N70D193G30B 1970mm - 4417lm White
- N70D193G02B 1970mm - 4417lm Anodized Grey
- N70D193G14B 1970mm - 4417lm Black
- N70D253G30B 2530mm - 5680lm White
- N70D253G02B 2530mm - 5680lm Anodized Grey
- N70D253G14B 2530mm - 5680lm Black
- N70D303G30B 3095mm - 6942lm White
- N70D303G02B 3095mm - 6942lm Anodized Grey
- N70D303G14B 3095mm - 6942lm Black
- N70DFC3G30B Flat Corner - 2524lm White
- N70DFC3G02B Flat Corner - 2524lm Anodized Grey
- N70DFC3G14B Flat Corner - 2524lm Black
- N70DEM3G30B Emergency - 3155lm White
- N70DEM3G02B Emergency - 3155lm Anodized Grey
- N70DEM3G14B Emergency - 3155lm Black

Mounting



- 08.0030

Suspension kit

One unit Suspension kit (L = 4 m). Maximum distance between the suspension cables: 2 m.

In-Finity 70 Suspension Down 3000K General Lighting . Accessories

Electrical



08.0031.00

Power supply rose

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable

In-Finity 70 Suspension Down 3000K General Lighting . Lamps



Top LED

Lamp category:


LED

Socket:

Special base

Lamp type:

Top LED



In-Finity 70 Suspension Down 3000K General Lighting

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- N70D053G30B 565mm - 1262lm White
- N70D053G02B 565mm - 1262lm Anodized Grey
- N70D053G14B 565mm - 1262lm Black
- N70D083G30B 845mm - 1893lm White
- N70D083G02B 845mm - 1893lm Anodized Grey
- N70D083G14B 845mm - 1893lm Black
- N70D113G30B 1125mm - 2524lm White
- N70D113G02B 1125mm - 2524lm Anodized Grey
- N70D113G14B 1125mm - 2524lm Black
- N70D143G30B 1405mm - 3155lm White
- N70D143G02B 1405mm - 3155lm Anodized Grey
- N70D143G14B 1405mm - 3155lm Black
- N70D163G30B 1690mm - 3786lm White
- N70D163G02B 1690mm - 3786lm Anodized Grey
- N70D163G14B 1690mm - 3786lm Black
- N70D193G30B 1970mm - 4417lm White
- N70D193G02B 1970mm - 4417lm Anodized Grey
- N70D193G14B 1970mm - 4417lm Black
- N70D253G30B 2530mm - 5680lm White
- N70D253G02B 2530mm - 5680lm Anodized Grey
- N70D253G14B 2530mm - 5680lm Black
- N70D303G30B 3095mm - 6942lm White
- N70D303G02B 3095mm - 6942lm Anodized Grey
- N70D303G14B 3095mm - 6942lm Black
- N70DFC3G30B Flat Corner - 2524lm White
- N70DFC3G02B Flat Corner - 2524lm Anodized Grey
- N70DFC3G14B Flat Corner - 2524lm Black
- N70DEM3G30B Emergency - 3155lm White
- N70DEM3G02B Emergency - 3155lm Anodized Grey
- N70DEM3G14B Emergency - 3155lm Black